

One Step Teak Cleaner & Brightener Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Revision Date: 05/20/2016 Date of issue: 10/03/2014

Version: 2.0

SECTION 1: IDENTIFICATION

Product Identifier

Product Name: One Step Teak Cleaner & Brightener

Product Code: 949XX

Intended Use of the Product

Use of the Substance/Mixture: Cleaner.

Name, Address, and Telephone of the Responsible Party

Starbrite® Inc.

4041 SW 47th Avenue Fort Lauderdale, FL 33314

(954)587-6280

www.starbrite.com

Emergency Telephone Number

Emergency Number: US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS-US classification

Eve Dam. 1 H318

Full text of hazard classes and H-statements: see section 16

Label Elements GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H318 - Causes serious eye damage.

Precautionary Statements (GHS-US): P280 - Wear eye protection, protective gloves, protective clothing.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call POISON CENTER/doctor.

Other Hazards

May be corrosive to respiratory tract. Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

MIMUIC			
Name	Product Identifier	% (w/w)	GHS-US classification
Oxalic acid	(CAS No) 144-62-7	5 – 10	Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Dermal), H312
			Eye Dam. 1, H318
Hydroxyacetic acid	(CAS No) 79-14-1	5 – 10	Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Inhalation:dust,mist), H332
			Skin Corr. 1B, H314
			Eye Dam. 1, H318
			Aquatic Acute 3, H402
Sulfonic acids, C14-16-alkane hydroxy and	(CAS No) 68439-57-6	1 - 2	Skin Irrit. 2, H315
C14-16-alkene, sodium salts			Eye Irrit. 2A, H319

EN (English US) 05/20/2016 IEITT.B-CC 1/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

			Aquatic Acute 2, H401
Triethanolamine	(CAS No) 102-71-6	0.1 - 1	Not classified

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible). **Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician. Obtain medical attention.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes serious eye damage.

Inhalation: Prolonged exposure may cause irritation.

Skin Contact: Prolonged exposure may cause skin irritation.

Eye Contact: Causes serious eye damage. Causes permanent damage to the cornea, iris, or conjunctiva.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand. If exposed or concerned, get medical advice and attention.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive, however in contact with incompatabilities may release explosive hydrogen gas.

Reactivity: Hazardous reactions will not occur under normal conditions. Adding water to solution may generate large amounts of heat. Reacts exothermically with (some) bases.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Do not allow run-off from fire fighting to enter drains or water courses. Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Nitrogen compounds. Sulfur compounds.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

05/20/2016 EITT.B-CC EN (English US) 2/10

^{*}A range of concentration as prescribed by Controlled Products Regulations has been used where necessary, due to varying composition. The specific chemical identity and/or exact percentage of composition has been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200].

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Emergency Procedures: Ventilate area. Stop leak if safe to do so.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Materials for Containment and Cleaning Up

For Containment: Cautiously neutralize spilled liquid. Absorb and/or contain spill with inert material, then place in suitable container. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13. See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Avoid breathing vapors, mist, and spray. Do not get in eyes, on skin, or on clothing.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong bases. Strong oxidizers. Metals.

Specific End Use(s)

Cleaner.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

governments, or the Mexican government		
Oxalic acid (144-62-7)		
Mexico	OELTWA (mg/m³)	1 mg/m ³
Mexico	OEL STEL (mg/m³)	2 mg/m ³
USA ACGIH	ACGIH TWA (mg/m³)	1 mg/m ³
USA ACGIH	ACGIH STEL (mg/m³)	2 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m³)	1 mg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1 mg/m ³
USA NIOSH	NIOSH REL (STEL) (mg/m³)	2 mg/m³
USA IDIH	US IDLH (mg/m³)	500 mg/m ³
Alberta	OEL STEL (mg/m³)	2 mg/m³
Alberta	OELTWA (mg/m³)	1 mg/m³
British Columbia	OEL STEL (mg/m³)	2 mg/m³ (anhydrous)
British Columbia	OELTWA (mg/m³)	1 mg/m³ (anhydrous)
Manitoba	OEL STEL (mg/m³)	2 mg/m³
Manitoba	OELTWA (mg/m³)	1 mg/m³
New Brunswick	OEL STEL (mg/m³)	2 mg/m³
New Brunswick	OELTWA (mg/m³)	1 mg/m³
Newfoundland & Labrador	OEL STEL (mg/m³)	2 mg/m³
Newfoundland & Labrador	OELTWA (mg/m³)	1 mg/m³
Nova Scotia	OEL STEL (mg/m³)	2 mg/m ³
Nova Scotia	OELTWA (mg/m³)	1 mg/m³
Nunavut	OEL STEL (mg/m³)	2 mg/m³
Nunavut	OEL TWA (mg/m³)	1 mg/m ³

05/20/2016 EIIT.B-CC EN (English US) 3/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Northwest Territories	OEL STEL (mg/m³)	2 mg/m³
Northwest Territories	OEL TWA (mg/m³)	1 mg/m³
Ontario	OEL STEL (mg/m³)	2 mg/m³
Ontario	OELTWA (mg/m³)	1 mg/m³
Prince Edward Island	OEL STEL (mg/m³)	2 mg/m³
Prince Edward Island	OELTWA (mg/m³)	1 mg/m³
Québec	VECD (mg/m³)	2 mg/m³
Québec	VEMP (mg/m³)	1 mg/m³
Saskatchewan	OEL STEL (mg/m³)	2 mg/m³
Saskatchewan	OEL TWA (mg/m³)	1 mg/m³
Yukon	OEL STEL (mg/m³)	2 mg/m³
Yukon	OELTWA (mg/m³)	1 mg/m³
Triethanolamine (102-71-6)		
USA ACGIH	ACGIH TWA (mg/m³)	5 mg/m ³
Alberta	OELTWA (mg/m³)	5 mg/m³
British Columbia	OELTWA (mg/m³)	5 mg/m³
Manitoba	OELTWA (mg/m³)	5 mg/m³
New Brunswick	OELTWA (mg/m³)	5 mg/m³
Newfoundland & Labrador	OELTWA (mg/m³)	5 mg/m³
Nova Scotia	OELTWA (mg/m³)	5 mg/m³
Northwest Territories	OEL STEL (mg/m³)	10 mg/m ³
Northwest Territories	OEL TWA (mg/m³)	5 mg/m³
Ontario	OELTWA (mg/m³)	3.1 mg/m ³
Ontario	OEL TWA (ppm)	0.5 ppm
Prince Edward Island	OELTWA (mg/m³)	5 mg/m³
Québec	VEMP (mg/m³)	5 mg/m³
Saskatchewan	OEL STEL (mg/m³)	10 mg/m ³
Saskatchewan	OELTWA (mg/m³)	5 mg/m³

Exposure Controls

Appropriate Engineering Controls: Ensure all national/local regulations are observed. Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits.

Personal Protective Equipment: Protective clothing. Gloves. Protective goggles. Insufficient ventilation: wear respiratory protection.









Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Other Information: When using, do not eat, drink or smoke

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State : Liquid
Appearance : Colorless
Odor : Characteristic
Odor Threshold : Not available

05/20/2016 EITT.B-CC EN (English US) 4/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

pH : 1.6

Evaporation Rate: Not availableMelting Point: Not availableFreezing Point: Not availableBoiling Point: Not availableFlash Point: > 100 °C (> 212 °F)

Auto-ignition Temperature Not available **Decomposition Temperature** Not available Flammability (solid, gas) Not available **Lower Flammable Limit** Not available **Upper Flammable Limit** Not available Not available **Vapor Pressure** Relative Vapor Density at 20 °C Not available Not available **Relative Density Specific Gravity** 1 (water = 1)

Solubility : Soluble in water.

Partition Coefficient: N-Octanol/Water : Not available

Viscosity : Not available

Explosion Data – Sensitivity to Mechanical Impact: Not expected to present an explosion hazard due to mechanical impact.

Explosion Data – Sensitivity to Static Discharge: Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

<u>Reactivity</u>: Hazardous reactions will not occur under normal conditions. Adding water to solution may generate large amounts of heat. Reacts exothermically with (some) bases.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight, extremely high or low temperatures, and incompatible materials. Contact with metallic

substances.

Incompatible Materials: Strong bases. Strong oxidizers. Metals.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Nitrogen compounds. Sulfur compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified ID50 and IC50 Data: Not available Skin Corrosion/Irritation: Not classified.

pH: 1.6

Serious Eye Damage/Irritation: Causes serious eye damage.

pH: 1.6

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified **Carcinogenicity:** Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: Causes serious eye damage. Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

05/20/2016 EITT.B-CC EN (English US) 5/10

Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Oxalic acid (144-62-7)			
ID50 Oral Rat	375 mg/kg		
ID50 Dermal Rat	20000 mg/kg		
Hydroxyacetic acid (79-14-1)			
ID50 Oral Rat	1950 mg/kg		
IC50 Inhalation Rat	3.6 mg/l/4h		
IC50 Inhalation Rat	1.76 mg/l/4h		
Triethanolamine (102-71-6)	Triethanolamine (102-71-6)		
ID50 Oral Rat	6400 mg/kg		
ID50 Dermal Rabbit	> 2000 mg/kg		
Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts (68439-57-6)			
ID50 Oral Rat	2310 mg/kg		
ID50 Dermal Rabbit	6300 mg/kg		
IC50 Inhalation Rat	> 52 mg/l/4h		
Triethanolamine (102-71-6)			
IARC Group	3		

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Not classified.

Oxalic acid (144-62-7)	
EC50 Daphnia 1	125 - 150 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
Hydroxyacetic acid (79-14-1)	
IC50 Fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 Daphnia 1	44 mg/l
Triethanolamine (102-71-6)	
IC50 Fish 1	10600 (10600 - 13000) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-
	through])
IC 50 Fish 2	1000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
ErC50 (algae)	169 mg/l
Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts (68439-57-6)	
IC50 Fish 1	4.2 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 Daphnia 1	4.53 mg/l (Ceriodaphnia sp)
IC 50 Fish 2	12.2 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
ErC50 (algae)	5.2 mg/l (Water quality - Marine Algal Growth Inhibition Test with Skeletonema costatum
	and Phaeodactylum tricornutum)

Persistence and Degradability

One Step Teak Cleaner & Brightener	
Persistence and Degradability	Not established.
Diagonymulative Detential	

Bioaccumulative Potential

One Step Teak Cleaner & Brightener		
Bioaccumulative Potential	Not established.	
Oxalic acid (144-62-7)	Oxalic acid (144-62-7)	
BCF Fish 1	(no bioaccumulation)	
Log Pow	-0.81 (at 30 °C)	
Hydroxyacetic acid (79-14-1)		
Log Pow	-1.11 (at 19 °C)	

05/20/2016 IEITT.B-CC EN (English US) 6/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Triethanolamine (102-71-6)	
BCF Fish 1	3.9
Log Pow	-2.53

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG/IMDG

UN Number Not regulated for transport

UN Proper Shipping Name Not regulated for transport

Transport Hazard Class(es)

Marine Pollutant : No

Additional Information Not available

Transport by sea Not regulated for transport

Air transport Not regulated for transport

In Accordance With IMDG Not regulated for transport

In Accordance With IATA/ICAO Not regulated for transport

In Accordance With TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

One Step Teak Cleaner & Brightener		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	
Oxalic acid (144-62-7)		
Listed on the United States TSCA (Toxic Substances Control Act)	inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test	
	rule under TSCA	
Hydroxyacetic acid (79-14-1)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Triethanolamine (102-71-6)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts (68439-57-6)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		

US State Regulations

Oxalic acid (144-62-7)

- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits TWAs
- RTK U.S. Massachusetts Right To Know List
- U.S. Michigan Occupational Exposure Limits STELs
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits STELs

05/20/2016 EITT.B-CC EN (English US) 7/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits TWAs
- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- **U.S. Oregon Permissible Exposure Limits TWAs**
- RTK U.S. Pennsylvania RTK (Right to Know) List
- U.S. South Carolina Toxic Air Pollutants Maximum Allowable Concentrations
- U.S. South Carolina Toxic Air Pollutants Pollutant Categories
- U.S. Tennessee Occupational Exposure Limits STELs
- U.S. Tennessee Occupational Exposure Limits TWAs
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- **U.S. Vermont Permissible Exposure Limits STELs**
- U.S. Vermont Permissible Exposure Limits TWAs
- **U.S. Washington Permissible Exposure Limits STELs**
- U.S. Washington Permissible Exposure Limits TWAs
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 25 Feet to Less Than 40 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 40 Feet to Less Than 75 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 75 Feet or Greater
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights Less Than 25 Feet

Hydroxyacetic acid (79-14-1)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Triethanolamine (102-71-6)

- RTK U.S. Massachusetts Right To Know List
- U.S. Minnesota Hazardous Substance List
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. North Dakota Air Pollutants Guideline Concentrations 8-Hour
- RTK U.S. Pennsylvania RTK (Right to Know) List
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 25 Feet to Less Than 40 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 40 Feet to Less Than 75 Feet
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights 75 Feet or Greater
- U.S. Wisconsin Hazardous Air Contaminants All Sources Emissions From Stack Heights Less Than 25 Feet

Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts (68439-57-6)

- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Canadian Regulations

One Step Teak Cleaner & Brightener

WHMIS Classification Class D Division 2 Subdivision B - Toxic material causing other toxic effects



05/20/2016 EITT.B-CC EN (English US) 8/10

Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Oxalic acid (144-62-7)		
Listed on the Canadian DSL (Domestic Substances List)		
Listed on the Canadian IDL (In	gredient Disclosure List)	
DL Concentration 0.1 %		
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects	
	Class E - Corrosive Material	
Hydroxyacetic acid (79-14-1)		
Listed on the Canadian DSL (D	omestic Substances List)	
Listed on the Canadian IDL (In	gredient Disclosure List)	
DL Concentration 1 %		
WHMIS Classification	Class E - Corrosive Material	
Triethanolamine (102-71-6)		
Listed on the Canadian DSL (Domestic Substances List)		
Listed on the Canadian IDL (Ingredient Disclosure List)		
IDL Concentration 1 %		
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria	
Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts (68439-57-6)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects	

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 05/20/2016

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
Н319	Causes serious eye irritation
Н332	Harmful if inhaled
H401	Toxic to aquatic life
H402	Harmful to aquatic life

05/20/2016 IEITT.B-CC EN (English US) 9/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

NFPA Health Hazard : 3 - Short exposure could cause serious temporary or


residual injury even though prompt medical attention was

given.

NFPA Fire Hazard : 0 - Materials that will not burn.

NFPA Reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



Party Responsible for the Preparation of This Document

Starbrite®

Phone Number: (954)587-6280

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS

05/20/2016 EITT.B-CC EN (English US) 10/10