AGM 12/270 (group Super 8D)



Product code: 62002700



In AGM batteries, the electrolyte (mixture of water and sulphuric acid) is largely absorbed in glass fibre. This type of battery is entirely maintenance-free and there is no gas formation with normal use. Not requiring any ventilation, AGM batteries can be installed anywhere.

Their construction gives a very fast discharge at very high currents so AGM batteries are ideal for systems that require high currents (for instance when starting an engine). The battery poles can be unscrewed and this type of battery can be combined with every standard battery terminal.

- · Excellent starter function.
- · Perfect upgrade for flooded lead acid batteries.
- \cdot Same initial power surge in an AGM 12/90 Ah as 180 Ah flooded lead-acid battery.
- · Glass-fibre technology ensures low internal resistance.
- · Use of thicker plates extends lifespan.
- \cdot Can be combined with every standard battery terminal.
- · Also for medium cyclical use.
- · Two year warranty.



Specifications

General specifications

Nominal battery voltage 12 V Nominal battery capacity C20 (battery capacity at a discharge time of 20 270 Ah

hours, till 10.5 V per battery)

Max. charge current76.5 ABattery terminalsM8

Outside dimensions, lxwxh (incl. handles, without automotive terminal post) $522 \times 268 \times 226 \text{ mm}$ post) $20.6 \times 10.6 \times 8.9 \text{ inch}$

Weight 73 kg 160.9 lb

Technical specifications

 CCA to DIN
 750 A

 CCA to SAE
 1200 A

