SAFETY DATA SHEET GRFAB49 Fabsil Universal Protector 5L

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name GRFAB49 Fabsil Universal Protector 5L

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Exterior surface coating.

1.3. Details of the supplier of the safety data sheet

Supplier Grangers International Ltd

Enterprise Way Duckmanton Derbyshire S44 5FD United Kingdom

T: +44 (0) 1773 521521 F: +44 (0) 1773 521262

info@grangersinternational.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0)1773 521521 (MON-FRI 08.00-17.00 UK TIME)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Flam. Liq. 3 - H226

Health hazards Eye Irrit. 2 - H319 Asp. Tox. 1 - H304

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms







Signal word

Danger

Hazard statements H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H304 May be fatal if swallowed and enters airways.

GRFAB49 Fabsil Universal Protector 5L

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing vapour/ spray.

P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTRE/doctor if you feel unwell.

P331 Do NOT induce vomiting.

P337+P313 If eye irritation persists: Get medical advice/ attention.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container in accordance with national regulations. HYDROCARBONS, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

P240 Ground and bond container and receiving equipment.

Supplementary precautionary statements

P241 Use explosion-proof electrical equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Contains

HYDROCARBONS, C10-C13, n-alkanes, isoalkanes, cyclics,

60-100%

<2% aromatics

CAS number: — EC number: 918-481-9

Classification

Asp. Tox. 1 - H304

Zirconium butanolate <1%

CAS number: 1071-76-7 EC number: 213-995-3

Classification

Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention if any discomfort continues.

GRFAB49 Fabsil Universal Protector 5L

Inhalation Move affected person to fresh air at once. Keep affected person under observation. When

breathing is difficult, properly trained personnel may assist affected person by administering

oxygen.

Ingestion Do not induce vomiting. Get medical attention. Give plenty of water to drink.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Get medical

attention if any discomfort continues.

Eye contact Rinse with water. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Vapours may cause headache, fatigue, dizziness and nausea. Irritating to respiratory system.

Ingestion May cause stomach pain or vomiting.

Skin contact Prolonged or repeated contact with skin may cause irritation, redness and dermatitis.

Eye contact May cause severe eye irritation. May cause blurred vision and serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances:

Carbon dioxide (CO2). Carbon monoxide (CO). Carbon.

5.3. Advice for firefighters

Protective actions during

firefighting

Cool containers exposed to flames with water until well after the fire is out.

Special protective equipment

for firefighters

Firefighter's clothing will provide a basic level of protection for chemical incidents. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Provide adequate ventilation. Wear protective gloves, eye and face protection. Avoid

inhalation of vapours and contact with skin and eyes. No smoking, sparks, flames or other sources of ignition near spillage. Wear protective clothing as described in Section 8 of this

safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Spillages or uncontrolled

discharges into watercourses must be reported immediately to the Environmental Agency or

other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

GRFAB49 Fabsil Universal Protector 5L

Methods for cleaning up Flush contaminated area with plenty of water. Take care as floors and other surfaces may

become slippery. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid inhalation of vapours/spray and contact with skin and eyes. Static electricity and

formation of sparks must be prevented.

Advice on general Do not smoke in work area. Good personal hygiene procedures should be implemented.

occupational hygiene Wash contaminated skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Store in tightly-closed, original container in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

DNEL Consumer - Dermal; Long term systemic effects: 125 mg/kg bw/day

Consumer - Oral; Long term systemic effects: 125 mg/kg bw/day Workers - Dermal; Long term systemic effects: 208 mg/kg bw/day Workers - Inhalation; Short term systemic effects: 871 mg/m³ Consumer - Inhalation; Long term systemic effects: 185 mg/m³

HYDROCARBONS, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Ingredient comments Advisory OEL. CEFIC-HSPA: 1200 mg/m3

DNEL According to information provided, the product does not have any harmful effects if

it is used and handled as specified.

8.2. Exposure controls

Protective equipment





Appropriate engineering

controls

Avoid inhalation of vapours. All handling should only take place in well-ventilated areas.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible.

Hand protection Wear protective gloves made of the following material: Nitrile: Thickness >0.3mm -

Permeation time according to EN 374-3:>60 minutes Polychloroprene.

Thickness >0.7mm - permeation time according to EN 374-3:>60 minutes For prolonged or

repeated contact: Nitrile: Thickness > 0.45mm - Permeation time according to EN 374-3: >480 minutes

GRFAB49 Fabsil Universal Protector 5L

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures Do not smoke in work area. Good personal hygiene procedures should be implemented.

Provide eyewash station. Wash contaminated skin thoroughly after handling.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn. When spraying, wear

a respirator fitted with the following cartridge: Particulate filter, type P1.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Clear, yellowish liquid.

Colourless to pale yellow.

Odour Solvent.

pH Not determined.Melting point Not determined.

Initial boiling point and range 149-213°C

Flash point 40°C Closed cup.

Evaporation rate Not applicable.

Relative density 0.78 @ 20°C

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

ReactivityNo test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

products

Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Static electricity and formation of sparks

must be prevented.

10.5. Incompatible materials

Materials to avoid Strong acids. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or

vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin corrosion/irritation

Skin corrosion/irritation Not determined.

Serious eye damage/irritation

GRFAB49 Fabsil Universal Protector 5L

Serious eye damage/irritation Not determined.

Respiratory sensitisation

Respiratory sensitisation Not determined.

Skin sensitisation

Skin sensitisation Not determined.

Carcinogenicity

Carcinogenicity Not applicable.

Reproductive toxicity

Reproductive toxicity - Does not contain any substances known to be toxic to reproduction.

development

Specific target organ toxicity - single exposure

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not known.

Aspiration hazard

Aspiration hazard Aspiration hazard if swallowed.

Inhalation Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal

tract. Harmful: may cause lung damage if swallowed.

Skin contact Prolonged contact may cause dryness of the skin.

Eye contact May cause eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Toxicity The product is not believed to present a hazard due to its physical nature.

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential No information available.

12.4. Mobility in soil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

GRFAB49 Fabsil Universal Protector 5L

General information Disposal of this product, process solutions, residues and by-products should at all times

comply with the requirements of environmental protection and waste disposal legislation and

any local authority requirements.

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. Do not empty into drains.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1268

UN No. (IMDG) 1268

UN No. (ICAO) 1268

UN No. (ADN) 1268

14.2. UN proper shipping name

Proper shipping name PETROLEUM DISTILLATES, N.O.S., or PETROLEUM PRODUCTS, N.O.S (Hydrocarbons,

(ADR/RID) C9-C11, n-alkanes, isoalkanes, cyclics, < 2%)

Proper shipping name (IMDG) PETROLEUM DISTILLATES, N.O.S., or PETROLEUM PRODUCTS, N.O.S (Hydrocarbons,

C9-C11, n-alkanes, isoalkanes, cyclics, < 2%)

Proper shipping name (ICAO) PETROLEUM DISTILLATES, N.O.S., or PETROLEUM PRODUCTS, N.O.S (Hydrocarbons,

C9-C11, n-alkanes, isoalkanes, cyclics, < 2%)

Proper shipping name (ADN) PETROLEUM DISTILLATES, N.O.S., or PETROLEUM PRODUCTS, N.O.S (Hydrocarbons,

C9-C11, n-alkanes, isoalkanes, cyclics, < 2%)

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group

ADN packing group

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

GRFAB49 Fabsil Universal Protector 5L

14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 3

Emergency Action Code 3Y

Hazard Identification Number

(ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

30

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Issued by Technical Manager

Revision date 21/03/2023

Revision 16

Supersedes date 28/02/2023

SDS number 4559

Hazard statements in full H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage. H319 Causes serious eye irritation. H335 May cause respiratory irritation.