



ACCESSORY RESOURCE GUIDE



ACCESSORY RESOURCE GUIDE
(3.2.2021)

Transducers

Transom Transducers.....	3-6
In-Hull Transducers.	6-7
Trolling Motor Transducers.....	7-11
Portable Transducers.....	11
S.S & Bronze Thru Hull Transducers.....	11-12
Plastic Thru Hull Transducers.....	12-14
Ice Transducers.	14
Trolling Motor Transducer Kit.....	15

Mounts, Hardware, Sensors

Transom Mounting Hardware & Adapters	16
Portable Mounting Hardware	16
In-Dash Mounts.....	17-19
Mounting Hardware	19-20
Temperature and Speed Sensors.	21

Cables






Extension Cables.	21-22
Power Cables.	22-23
Transducer Adapter Cables.....	24-25
Ethernet Cables.....	25-27

Other Accessories and Systems






MEGA 360 Imaging.....	28-30
MEGA Live Imaging	
Advanced Fishing Systems.....	30-34
Unit Covers.....	34-36
Portable Configurations.....	37
Ice Accessories.	37-38
Autopilot and Accessories.	38-40
Radar	40






TRANSOM TRANSDUCERS – 2D Sonar	Item Number	Description	Compatible Units
 <p>XNT 9 HW T</p>	710274-1	Transom mount Dual Spectrum CHIRP Transducer with temperature sensor and 20' cable	<ul style="list-style-type: none"> • All HELIX models with CHIRP <ul style="list-style-type: none"> ○ G2 / G2N and newer models • All ICE HELIX models with CHIRP <ul style="list-style-type: none"> ○ G2/G2N and newer models
 <p>XNT 14 HW T</p>	710285-1	Transom mount Dual Spectrum CHIRP transducer with temperature sensor and 20' cable	<ul style="list-style-type: none"> • APEX 13 / 16 / 19 Series <ul style="list-style-type: none"> ○ All Models • SOLIX 10 / 12 / 15 Series <ul style="list-style-type: none"> ○ All G2 / G3 Models
 <p>XNT 9 20 T</p>	710198-1	Transom Mount Single/Dual Beam 20/60 Degree 200/83kHz Temperature Sensor	<ul style="list-style-type: none"> • All 100, 300, 500, 600, 700, 800, 900, 1100 except DI models • All HELIX Series except DI models
 <p>XNT 9 28 T</p>	710236-1	Transom mount Dual Beam, 28/16 Degree, 200/455kHz, Temp	<ul style="list-style-type: none"> • PiranhaMAX 4 and PiranhaMAX 4 PT
 <p>XNT 9 DB 74 T</p>	710237-1	Transom mount Dual Beam, 20/74 Degrees, 200/50 kHz with built in temp for use with extended depth models	<ul style="list-style-type: none"> • 1159ci HD XD Combo • 859ci HD XD Combo • 678c HD XD • 688ci HD XD Combo • 959ci HD XD Combo • All HELIX models except HELIX 7 SONAR G2, HELIX 7 SI GPS, HELIX 7 DI GPS, HELIX 7 SONAR GPS, HELIX 7 DI, HELIX 5 DI G2, HELIX 5 SI GPS, HELIX 5 DI GPS, HELIX 5 SONAR GPS, HELIX 5 DI, HELIX 5 SONAR





 <p>XNT 14 20 T</p>	710247-1	Transom mount Dual Beam transducer 20/60 degree, 200/83 kHz, temp included	<ul style="list-style-type: none"> • ION* Series • ONIX10ci COMBO • ONIX 10ci COMBO NT • ONIX8ci COMBO • ONIX 8ci COMBO NT • SOLIX 10 CHIRP GPS • SOLIX 12 CHIRP GPS • SOLIX 15 CHIRP GPS <p>*Must also have the Sonar Module</p>
TRANSOM TRANSDUCERS – Down Imaging			
 <p>XNT 9 HW MDI 75 T</p>	710295-1	Transom Mount transducer with MEGA Down Imaging, Dual Spectrum CHIRP, temperature sensor and 20' cable	<ul style="list-style-type: none"> • HELIX 7 and 8 CHIRP MDI <ul style="list-style-type: none"> o G3 / G3N and newer models
 <p>XM 9 HW MDI T</p>	710280-1	Transom Mount transducer with MEGA Down Imaging+, Dual Spectrum CHIRP, temperature sensor and 20' cable	<ul style="list-style-type: none"> • HELIX 9 / 10 / 12 CHIRP MEGA DI+ <ul style="list-style-type: none"> o G3 / G3N and newer models
 <p>XM 14 HW MDI T</p>	710290-1	Transom Mount transducer with MEGA Down Imaging+, Dual Spectrum CHIRP, temperature sensor and 20' cable	<ul style="list-style-type: none"> • SOLIX G2 & G3 Series <ul style="list-style-type: none"> o All models (provides 2D & MDI+ only) • APEX 13 / 16 / 19 Series <ul style="list-style-type: none"> o All models (provides 2D & MDI+ only)
 <p>XM 9 MDI T</p>	710269-1	Transom mount MEGA DI, DualBeam PLUS, 20/60/86/55 degrees, 200/83/455/800 kHz and 1.2 MHz, temperature built-in	<ul style="list-style-type: none"> • HELIX 9 CHIRP MEGA DI GPS G2N • HELIX 10 CHIRP MEGA DI GPS G2N • HELIX 12 CHIRP MEGA DI GPS G2N

 <p>XNT 9 DI T</p>	710226-1	Transom Mount Down Imaging 83/200/455 kHz Temperature Sensor	<ul style="list-style-type: none"> • 1159ci HD DI, 959ci HD DI, 859ci HD DI, 571 HD DI, 561 DI, 386ci DI, 346c DI, 688ci DI, 678 DI, 1158c DI, 958c HD DI, 958c DI, 858c HD DI, 858c DI, 798ci SI and 798ci HD SI and 899ci HD SI • PiranhaMAX 4 DI • All HELIX non-CHIRP DI models
TRANSOM TRANSDUCERS – Side Imaging			
	Item Number	Description	Compatible Units
 <p>XNT 9 HW MSI 150 T</p>	710297-1	Transom mount MEGA Side Imaging, MEGA Down Imaging, Dual Spectrum CHIRP transducer with temperature sensor and 20' cable	<ul style="list-style-type: none"> • HELIX 7 CHIRP MSI models <ul style="list-style-type: none"> o G3/G3N and newer models
 <p>XM 9 HW MSI T</p>	710282-1	Transom mount MEGA Side Imaging+, MEGA Down Imaging+, Dual Spectrum CHIRP transducer with temperature sensor and 20' cable	<ul style="list-style-type: none"> • HELIX 8 / 9 / 10 / 12 / 15 CHIRP MSI+ <ul style="list-style-type: none"> o G3N and G4N models only
 <p>XM 14 HW MSI T</p>	710292-1	Transom mount MEGA Side Imaging+, MEGA Down Imaging+, Dual Spectrum CHIRP transducer with temperature sensor and 20' cable	<ul style="list-style-type: none"> • APEX 13 / 16 / 19 Series <ul style="list-style-type: none"> o All models • SOLIX 10 / 12 / 15 MEGA SI+ <ul style="list-style-type: none"> o G2 and G3 models
 <p>XM 9 20 MSI T</p>	710262-1	Transom mount MEGA SI, MEGA DI, DualBeam PLUS, 20/60/86/55 degrees, 200/83/455/800 kHz and 1.2 MHz, temperature built-in	<ul style="list-style-type: none"> • HELIX 9 CHIRP MEGA SI GPS G2N • HELIX 10 CHIRP MEGA SI GPS G2N • HELIX 12 CHIRP MEGA SI GPS G2N


 <p>XM 14 20 MSI T</p>	710265-1	<p>Transom mount MEGA SI, MEGA DI, DualBeam PLUS, 20/60/86/55 degrees, 200/83/455/800 kHz and 1.2 MHz, temperature built-in</p>	<ul style="list-style-type: none"> • SOLIX 10 MEGA SI GPS • SOLIX 12 MEGA SI GPS • SOLIX 15 MEGA SI GPS
 <p>XHS 9 HDSI 180 T</p>	710201-1	<p>Transom Mount Dual/HD Side Imaging 20/74/84 Degree 200/83/455/800 kHz Temperature Sensor</p>	<ul style="list-style-type: none"> • 1199ci SI, 999ci HD SI, 898c HD SI, 899ci HD SI, 998c HD SI • HELIX 9 SI GPS • HELIX 10 SI GPS • HELIX 12 SI GPS
 <p>XNT 9 SI 180 T</p>	710200-1	<p>Transom Mount Compact Dual/Side Imaging 20/74/84 Degree 83/200/455/800 kHz Temperature Sensor</p>	<ul style="list-style-type: none"> • 398C SI, 698ci HD SI, 798ci SI, 899CI HD SI • HELIX 5 SI GPS • HELIX 5 CHIRP SI GPSG2 • HELIX 7 SI GPS • HELIX 7 CHIRP SI GPSG2 • HELIX 7 CHIRP SI GPSG2N • HELIX 9 SI GPS
<p>IN-HULL TRANSDUCERS – 2D sonar</p>	<p>Item Number</p>	<p>Description</p>	<p>Compatible Units</p>
 <p>XP 9 HW</p>	710275-1	<p>In-Hull Dual Spectrum CHIRP Narrow Beam - 25 Degrees, 180-240 kHz Wide Beam - 42 Degrees, 140-200 kHz</p>	<ul style="list-style-type: none"> • HELIX 5 CHIRP G2 (GPS models) • HELIX 7 CHIRP G2/G3 models • HELIX 7 CHIRP G2N/G3N models • HELIX 8 G3N/G4N models • HELIX 9 G2N/G3N/G4N models • HELIX 10 G2N/G3N/G4N models • HELIX 12 G2N/G3N/G4N models • HELIX 15 G4N models • ICE HELIX CHIRP G2/G3/G3N models
 <p>XP 9 HW T</p>	710276-1	<p>In-Hull Dual Spectrum CHIRP Narrow Beam - 25 Degrees, 180-240 kHz Wide Beam - 42 Degrees, 140-200 kHz with Temperature Sensor</p>	<ul style="list-style-type: none"> • HELIX 5 CHIRP G2 (GPS models) • HELIX 7 CHIRP G2/G3 models • HELIX 7 CHIRP G2N/G3N models • HELIX 8 G3N/G4N models • HELIX 9 G2N/G3N/G4N models • HELIX 10 G2N/G3N/G4N models • HELIX 12 G2N/G3N/G4N models • HELIX 15 G4N models • ICE HELIX CHIRP G2/G3/G3N models

 <p>XP 14 HW</p>	710286-1	<p>In-Hull Dual Spectrum CHIRP Narrow Beam - 25 Degrees, 180-240 kHz Wide Beam - 42 Degrees, 140-200 kHz</p>	<ul style="list-style-type: none"> • APEX 13 / 16 / 19 Series <ul style="list-style-type: none"> ○ All models • SOLIX 10 / 12 / 15 Series <ul style="list-style-type: none"> ○ G2 / G3 models
 <p>XP 14 HW T</p>	710287-1	<p>In-Hull Dual Spectrum CHIRP Narrow Beam - 25 De- grees, 180-240 kHz Wide Beam - 42 Degrees, 140-200 kHz Temperature Sensor</p>	<ul style="list-style-type: none"> • APEX 13 / 16 / 19 Series <ul style="list-style-type: none"> ○ All models • SOLIX 10 / 12 / 15 Series <ul style="list-style-type: none"> ○ G2 / G3 models
 <p>XP 9 20 T</p>	710147-1	<p>In-Hull Mount Single or Dual Beam 20°/60° 200/83 kHz Temp. Sensor Pigtail</p>	<ul style="list-style-type: none"> • All 100 and 300 Series except DI • All 500 Series except DI • All 600 Series except DI • All 700 Series except DI • All 800 Series except DI • All 900 Series except DI, models • All 1100 Series except DI models • All HELIX Series except DI models • HDR650
 <p>XP 14 20 T</p>	710248-1	<p>In-Hull transducer Dual Beam, 20/60 degrees, 200/83 kHz, temp pigtail. For use in single layer fiberglass hull boats</p>	<ul style="list-style-type: none"> • All ONIX Series • SOLIX 10 CHIRP GPS • SOLIX 12 CHIRP GPS • SOLIX 15 CHIRP GPS • ION* Series *Must also have the Sonar Module
<p>TROLLING MOTOR TRANSDUCERS– 2D Sonar</p>	<p>Item Number</p>	<p>Description</p>	<p>Compatible Units</p>
 <p>XTM 9 HW T</p>	710277-1	<p>Trolling Motor Mount Dual Spectrum CHIRP Narrow Beam - 25 Degrees, 180-240 kHz Wide Beam - 42 Degrees, 140-200 kHz temperature Sensor</p>	<ul style="list-style-type: none"> • HELIX 5 CHIRP G2 (GPS models) • HELIX 7 CHIRP G2/G3 models • HELIX 7 CHIRP G2N/G3N models • HELIX 8 G3N/G4N models • HELIX 9 G2N/G3N/G4N models • HELIX 10 G2N/G3N/G4N models • HELIX 12 G2N/G3N/G4N models • HELIX 15 G4N models • ICE HELIX CHIRP G2/G3/G3N models

 <p>XTM 14 HW T</p>	710288-1	<p>Trolling Motor Mount Dual Spectrum CHIRP Narrow Beam - 25 Degrees, 180-240 kHz Wide Beam - 42 Degrees, 140-200 kHz 20' cable with temperature sensor</p>	<ul style="list-style-type: none"> • APEX 13 / 16 / 19 Series <ul style="list-style-type: none"> ○ All models • SOLIX 10 / 12 / 15 Series <ul style="list-style-type: none"> ○ G2 / G3 models
 <p>XTM 9 20 T</p>	710160-1	<p>Trolling Motor Mount Single/Dual Beam 20/60 Degree 200/83kHz 20' cable and with temp</p>	<ul style="list-style-type: none"> • All 100 and 300 Series except DI • All 500 Series except DI models • All 600 Series except DI models • All 700 Series except DI models • All 800 Series except DI models • All 800 Series except DI models • All 900 Series except DI, 3D models • All 1100 Series except DI • All HELIX Series except DI
 <p>XTM 9 28 T</p>	710246-1	<p>Trolling Motor Mount Dual Beam, 28/16 Degree, 200/455kHz, 20' cable and temperature sensor</p>	<ul style="list-style-type: none"> • PiranhaMAX 4, PiranhaMAX 4 PT
 <p>XTM 14 20 T</p>	710250-1	<p>Trolling Motor Mount Dual Beam, 20/60 degrees, 200/83 kHz, 20' cable and temperature sensor</p>	<ul style="list-style-type: none"> • SOLIX 10 Series - G1 Models • SOLIX 12 Series - G1 Models • SOLIX 15 Series – G1 Models • ION Series * • All ONIX Series <p>*Must also have the Sonar Module</p>
<p>TROLLING MOTOR TRANSDUCERS– Down Imaging</p>	<p>Item Number</p>	<p>Description</p>	<p>Compatible Units</p>
 <p>XTM 9 HW MDI 75 T</p>	710296-1	<p>Trolling Motor Mount MEGA Down Imaging, Dual Spectrum CHIRP and temperature sensor</p>	<ul style="list-style-type: none"> • HELIX 7 CHIRP MEGA DI GPS G3 • HELIX 7 CHIRP MEGA DI GPS G3N • HELIX 8 CHIRP MEGA DI GPS G3N • HELIX 8 CHIRP MEGA DI GPS G4N






 <p>XTM 9 HW MDI T</p>	<p>710281-1</p>	<p>Trolling Motor Mount MEGA Down Imaging+ Dual Spectrum CHIRP temperature Sensor</p>	<ul style="list-style-type: none"> • HELIX 8 MEGA DI GPS G3N • HELIX 8 MEGA DI GPS G4N • HELIX 9 MEGA DI+ G3N • HELIX 9 MEGA DI+ G4N • HELIX 10 MEGA DI+ G3N • HELIX 10 MEGA DI+ G4N • HELIX 12 MEGA DI+ G3N • HELIX 12 MEGA DI+ G4N • HELIX 15 MEGA DI+ G4N CHO
 <p>XTM 14 HW MDI T</p>	<p>710291-1</p>	<p>Trolling Motor Mount MEGA Down Imaging+ Dual Spectrum CHIRP 20' cable with temperature sensor</p>	<ul style="list-style-type: none"> • APEX 13 / 16 / 19 Series <ul style="list-style-type: none"> ◦ All models (provides 2D & MDI+ only) • SOLIX G2 / G3 Series <ul style="list-style-type: none"> ◦ All models (provides 2D & MDI+ only)
 <p>XTM 9 MDI T</p>	<p>710270-1</p>	<p>Trolling Motor Mount MEGA Down Imaging, DualBeam sonar transducer with temperature sensor</p>	<ul style="list-style-type: none"> • HELIX 9 MEGA DI G2N • HELIX 10 MEGA DI G2N • HELIX 12 MEGA DI G2N
 <p>XTM 9 DI 25 T</p>	<p>710234-1</p>	<p>Trolling Motor Mount Down Imaging/ DualBeam Plus 75/45/ 25/16 Degree 200/455 kHz 455/800 kHz (DI) 20' cable, with temp sensor</p>	<ul style="list-style-type: none"> • HELIX 7 DI GPS • HELIX 7 DI GPS G2 • HELIX 9 DI GPS • HELIX 10 DI GPS • HELIX 12 CHIRP DI GPS • 1159ci HD DI • 959ci HD DI • 859ci HD DI • 688ci DI, 678 DI • 386ci DI, 346c DI • PMAX 4 DI

 <p>XTM 9 WIDE DI 20 T</p>	710235-1	Trolling Motor Mount Down Imaging/ DualBeam 75/45/ 25/16 Degree 200/455 kHz 455/800 kHz (DI), 20' cable with temperature sensor	<ul style="list-style-type: none"> • HELIX 7 DI GPS • HELIX 7 DI GPS G2 • HELIX 9 DI GPS • HELIX 10 DI GPS • HELIX 12 CHIRP DI GPS • 1159ci HD DI • 959ci HD DI • 859ci HD DI
TROLLING MOTOR TRANSDUCERS– Side Imaging	Item Number	Description	Compatible Units
 <p>XTM 9 HW MSI 150 T</p>	710298-1	Trolling Motor Mount MEGA Side Imaging MEGA Down Imaging Dual Spectrum CHIRP with temperature Sensor	<ul style="list-style-type: none"> • HELIX 7 MSI GPS G3 • HELIX 7 MSI GPS G3N
 <p>XTM 9 HW MSI T</p>	710283-1	Trolling Motor Mount MEGA Side Imaging+ MEGA Down Imaging+ Dual Spectrum CHIRP with 20' cable and temperature sensor	<ul style="list-style-type: none"> • HELIX 8 MEGA SI+ GPS G3N • HELIX 8 MEGA SI+ GPS G4N • HELIX 9 MEGA SI+ GPS G3N • HELIX 9 MEGA SI+ GPS G4N • HELIX 10 MEGA SI+ GPS G3N • HELIX 10 MEGA SI+ GPS G4N • HELIX 12 MEGA SI+ GPS G3N • HELIX 12 MEGA SI+ GPS G4N • HELIX 15 MEGA SI+ GPS G4N
 <p>XTM 9 20 MSI T</p>	710263-1	Trolling Motor Mount 1.2 Mhz/800 kHz/455 kHz MEGA SI, MEGA DI and DualBeam Plus 20' cable with temperature sensor	<ul style="list-style-type: none"> • HELIX 9 MEGA SI GPS G2N • HELIX 10 MEGA SI GPS G2N • HELIX 12 MEGA SI GPS G2N






 <p>XTM 9 HDSI 180 T</p>	710205-1	<p>Trolling Motor Mount Dual/HD Side Imaging 20/74/180 Degree 83/200/455/800kHz 20' cable and with temp</p>	<ul style="list-style-type: none"> • HELIX 9 SI GPS • HELIX 10 SI GPS • HELIX 12 SI GPS • 1199ci HD SI, 999ci HD SI, 899ci HD SI
 <p>XTM 9 SI 180 T</p>	710204-1	<p>Trolling Motor Mount Compact SI / DI and DualBeam 20/60/70 Degree 83/200/455/800kHz 20' cable and with temp</p>	<ul style="list-style-type: none"> • HELIX 9 SI GPS • HELIX 7 SI GPS • HELIX 7 SI GPS G2 • HELIX 7 SI GPS G2N • HELIX 5 SI GPS • HELIX 5 SI GPS G2 • 398ci SI, 698ci HD SI, 899ci HD SI
<p>PORTABLE TRANSDUCERS</p>	<p>Item Number</p>	<p>Description</p>	<p>Compatible Units</p>
 <p>XPT 9 HW T</p>	710278-1	<p>Portable, suction cup mount, Dual Spectrum CHIRP transducer with Temperature sensor and 20' cable.</p>	<ul style="list-style-type: none"> • HELIX 5 CHIRP G2 models • HELIX 7 CHIRP G2/G3 models • HELIX 7 G2N/G3N models • HELIX 8 G3N/G4N models • HELIX 9 G2N/G3N/G4N models • HELIX 10 G2N/G3N/G4N models • HELIX 12 G2N/G3N/G4N models • HELIX 15 G4N models • ICE HELIX CHIRP G2/G2N/G3/G3N models
 <p>XPT 9 20 T</p>	710161-1	<p>Portable, suction cup mount, Dual Beam transducer with Temperature sensor and 20' cable.</p>	<ul style="list-style-type: none"> • All 100 / 300 Series except DI models • All 500 Series except DI models • All 600 Series except DI models • All 800 Series except DI models • All 900 Series except DI models • All 1100 Series except DI models • All HELIX non-CHIRP models, except DI • HDR 650
<p>S.S. & BRONZE THRU HULL TRANSDUCERS – 2D Sonar</p>	<p>Item Number</p>	<p>Description</p>	<p>Compatible Units</p>
 <p>XTH 9 20</p>	710166-1	<p>Bronze thru-hull transducer with Dual Beam sonar, temp sensor and 20' cable. 20/60 Degree, 200/83kHz</p>	<ul style="list-style-type: none"> • All 100 / 300 Series except DI models • All 500 Series except DI models • All 600 Series except DI models • All 800 Series except DI models • All 900 Series except DI models • All 1100 Series except DI models • All HELIX non-CHIRP models, except DI models

S.S. & BRONZE THRU HULL TRANSDUCERS – Side Imaging	Item Number	Description	Compatible Units
 <p>SSTH 14 HW MSI+ T</p>	710302-1	Stainless Steel thru-hull transducer with MEGA Side Imaging+, MEGA Down Imaging+ and Dual Spectrum CHIRP sonar and includes built-in temperature sensor, fairing block, stainless steel mounting hardware and 20' cable,	<ul style="list-style-type: none"> • APEX 13 / 16 / 19 Series <ul style="list-style-type: none"> ○ All models • SOLIX 10 / 12 / 15 MEGA SI+ Series <ul style="list-style-type: none"> ○ G2/G3 models
PLASTIC THRU- HULL TRANSDUCERS – 2D Sonar	Item Number	Description	Compatible Units
 <p>XPTH 9 HW T</p>	710279-1	Plastic thru-hull transducer Dual Spectrum CHIRP, temperature Sensor and 20' cable	<ul style="list-style-type: none"> • HELIX 5 G2 (GPS models) • HELIX 7 G2/G3 models • HELIX 7 G2N/G3N models • HELIX 8 G3N/G4N models • HELIX 9 G2N/G3N/G4N models • HELIX 10 G2N/G3N/G4N models • HELIX 12 G2N/G3N/G4N models • HELIX 15 G4N models • ICE HELIX G2/G3/G3N models
 <p>XPTH 14 HW T</p>	710289-1	Plastic thru-hull transducer Dual Spectrum CHIRP, temperature Sensor and 20' cable	<ul style="list-style-type: none"> • APEX 13 / 16 / 19 Series <ul style="list-style-type: none"> ○ All models • SOLIX 10 / 12 / 15 Series <ul style="list-style-type: none"> ○ All models
 <p>XTH 9 20 P</p>	710167-1	Plastic thru-hull Single/Dual Beam transducer with 20' cable. 20/60 Degree, 200/83kHz Transducer: 3.9" L x 2.5" W x 1.16" D Shaft: 1.0" diameter	<ul style="list-style-type: none"> • All HELIX non-CHIRP models, except DI models • All 300 Series except DI models • All 500 Series except DI models • All 600 Series except DI models • All 800 Series except DI models • All 900 Series except DI, 3D models • All 1100 Series except DI models

 <p>XTH 9 20 P</p>	710181-1	<p>Plastic flush mount thru the hull transducer. DualBeam, 20/60 degree, 200/83kHz</p>	<ul style="list-style-type: none"> • All HELIX non-CHIRP models, except DI models • All 300 Series except DI models • All 500 Series except DI models • All 600 Series except DI models • All 800 Series except DI models • All 900 Series except DI, 3D models • All 1100 Series except DI models
 <p>XTH 9 DB 74 P</p>	710185-1	<p>Plastic thru hull Dual Beam, 20/74 degrees. 200/50kHz, transducer with 20' cable 6.7" L x 3" W x 1.4" D (below boat hull). Shaft: 1" diameter. Cable Length: 30 Feet.</p>	<ul style="list-style-type: none"> • 1159ci HD XD Combo • 859ci HD XD Combo • 678c HD XD • 688ci HD XD Combo • 959ci HD XD Combo • All HELIX models except HELIX 7 SONAR G2, HELIX 7 SI GPS, HELIX 7 DI GPS, HELIX 7 SONAR GPS, HELIX 7 DI, HELIX 5 DI G2, HELIX 5 SI GPS, HELIX 5 DI GPS, HELIX 5 SONAR GPS, HELIX 5 DI, HELIX 5 SONAR
<p>PLASTIC THRU- HULL TRANSDUCERS – Side Imaging</p>	<p>Item Number</p>	<p>Description</p>	<p>Compatible Units</p>
 <p>XPTH 9 HW MSI T</p>	710284-1	<p>Plastic thru-hull transducer MEGA SIDE IMAGING+, MEGA Down Imaging+ Dual Spectrum CHIRP, temperature Sensor and 20' cable</p>	<ul style="list-style-type: none"> • HELIX 8 MEGA SI+ GPS G3N • HELIX 8 MEGA SI+ GPS G4N • HELIX 9 MEGA SI+ GPS G3N • HELIX 9 MEGA SI+ GPS G4N • HELIX 10 MEGA SI+ GPS G3N • HELIX 10 MEGA SI+ GPS G4N • HELIX 12 MEGA SI+ GPS G3N • HELIX 12 MEGA SI+ GPS G4N • HELIX 15 MEGA SI+ GPS G4N
 <p>XPTH 14 HW MSI T</p>	710294-1	<p>Plastic thru-hull transducer MEGA SIDE IMAGING+, MEGA Down Imaging+ Dual Spectrum CHIRP, temperature Sensor and 20' cable</p>	<ul style="list-style-type: none"> • APEX 13 / 16 / 19 Series <ul style="list-style-type: none"> ○ All models • SOLIX 10 / 12 / 15 MEGA SI+ <ul style="list-style-type: none"> ○ G2/G3 models

 <p>XPTH 9 20 MSI T</p>	710264-1	Plastic Thru Hull MEGA SI / MEGA DI / DualBeam Transducer includes 1.2 Mhz/800 kHz/455 kHz with 20' cable and temp sensor	<ul style="list-style-type: none"> • HELIX 9 MEGA SI GPS G2N • HELIX 10 MEGA SI GPS G2N • HELIX 12 MEGA SI GPS G2N
 <p>XPTH 14 20 MSI T</p>	710267-1	Plastic thru hull MEGA SI / DI and DualBeam Plus transducer with temp sensor	<ul style="list-style-type: none"> • SOLIX 10 CHIRP MEGA SI GPS • SOLIX 12 CHIRP MEGA SI GPS • SOLIX 15 CHIRP MEGA SI GPS • ONIX Series* <p>*Only 455/800 kHz frequencies available for SI and DI</p>
ICE TRANSDUCERS- 2D Sonar	Item Number	Description	Compatible Units
 <p>XI 9 1521</p>	710273-1	Dual Spectrum CHIRP Ice Transducer with 8' cable. 130-250 kHz 15 - 21 Degree.	<ul style="list-style-type: none"> • All ICE HELIX CHIRP G2/G2N/G3/G3N models • All HELIX CHIRP G2/G2N/G3/G3N/G4N models in Ice Fishing Mode
 <p>XI 9 20</p>	710211-1	Dual Beam Ice transducer with 8' cable. 20/60 Degree, 200/83 kHz.	<ul style="list-style-type: none"> • All non-CHIRP HELIX units, except DI models • All 100 and 300 Series™ except DI • All 500, 600, 700, 800, 900, 1100 Series, except DI and 3D models
 <p>XI 9 19</p>	710215-1	Dual Beam Ice transducer with 8' cable. 9/19 Degree. 455/240kHz.	<ul style="list-style-type: none"> • ICE 35 • ICE 45 • ICE 55








TROLLING MOTOR TRANSDUCER KIT	Item Number	Description	Compatible Units
 <p>AD MTM HW MDI</p>	740181-1	<p>MEGA DI+ Trolling Motor Transducer Adapter Bracket</p> <p>Rugged composite design conforms to the trolling motor for low profile fit. Adapts transom mount transducer for trolling motor use</p>	<p>Transducers:</p> <ul style="list-style-type: none"> • XM 9 HW MDI T • XTM 9 HW MDI T • XM 14 HW MDIT • XTM 14 HW MDI T <p>Fish Finders:</p> <ul style="list-style-type: none"> • HELIX 8/9/10/12/15 MEGA DI+ GPS G4N <ul style="list-style-type: none"> ○ G3N / G4N Series • SOLIX 10 / 12 / 15 Series <ul style="list-style-type: none"> ○ G2/G3 Models • APEX 13 / 16 / 19 Series <ul style="list-style-type: none"> ○ All Models
 <p>AD MTM HW MSI</p>	740182-1	<p>MEGA SI+ Trolling Motor Transducer Adapter Bracket</p> <p>Rugged composite design conforms to the trolling motor for low profile fit. Adapts transom mount transducer for trolling motor use</p>	<p>Transducers:</p> <ul style="list-style-type: none"> • XM 9 HW MSI T • XTM 9 HW MSI T • XM 14 HW MSI T • XTM 14 HW MSI T <p>Fish Finders:</p> <ul style="list-style-type: none"> • HELIX 8/9/10/12/15 MEGA SI+ GPS G4N <ul style="list-style-type: none"> ○ G3N / G4N Series • SOLIX 10 / 12 / 15 Series <ul style="list-style-type: none"> ○ G2/G3 Models • APEX 13 / 16 / 19 Series <ul style="list-style-type: none"> ○ All Models
 <p>AD MTM</p>	740159-1	<p>Rugged Trolling Motor Transducer Adapter Bracket</p>	<p>Transducers:</p> <ul style="list-style-type: none"> • XM 9 20 MSI T • XM 14 20 MSI T <p>Fish Finders:</p> <ul style="list-style-type: none"> • HELIX 9 CHIRP MEGA SI GPS G2N • HELIX 10 CHIRP MEGA SI GPS G2N • HELIX 12 CHIRP MEGA SI GPS G2N • SOLIX 10 SI • SOLIX 12 SI • SOLIX 15 SI
 <p>AD XTM 9</p>	740087-1	<p>Trolling Motor Adapter for New XNT Transducer</p>	<p>Transducers:</p> <ul style="list-style-type: none"> • XNT 9 20 • XNT 9 20 T • XNT 9 SI 180 T • XNT 9 DI T • XNT 9 28 T • XNT 9 HW T • XNT 14 20 T • XNT 14 DI T • XNT 9 QB 90 T

TRANSOM MOUNTING HARDWARE & ADAPTERS	Item Number	Description	Compatible Units
 <p>MHX XM HW</p>	740183-1	<p>MEGA Imaging+ Metal Mounting Bracket Durable and rugged metal construction Allows adjustment of transducer angle Ideal for transom-mount installations</p>	<p>Transducers:</p> <ul style="list-style-type: none"> • XM 9 HW MSI T • XM 9 HW MDIT • XM 9 20 MSI T • XM 14 HW MDIT • XM 14 HW MSIT • XM 14 20 MSI T • XM 14 74 MSIT
 <p>MHX MXNT</p>	740162-1	<p>Durable and rugged metal construction Impact-Release Mounting Bracket</p>	<p>Transducers:</p> <ul style="list-style-type: none"> • XNT 9 DI T • XNT 9 28 T • XNT 9 20 T • XNT 9 HW T • XNT 14 20 T • XNT 14 74 T • XNT 14 DI T
 <p>MHX HS</p>	740011-1	<p>HDWE - High Speed 200 KHZ Metal & Plastic</p>	<p>Transducers:</p> <ul style="list-style-type: none"> • XHS 9 DB 74 T • XHS 9 SI 160 T • XHS 9 HDSI 180T • XT 14 20 HDSI T • XT 14 74 HDSI T
 <p>MHX XNT</p>	740093-1	<p>HDWE - XNT with kick-up</p>	<p>Transducers:</p> <ul style="list-style-type: none"> • XNT 9 DI T • XNT 9 28 T • XNT 9 20 T • XNT 9 20 • XNT 9 HW T • XNT 14 20 T • XNT 14 74 T • XNT 14 DI T
PORTABLE MOUNTING HARDWARE	Item Number	Description	Compatible Units
 <p>MHX XNPT</p>	740090-1	<p>Transom transducer mounting hardware</p>	<p>Transducers:</p> <ul style="list-style-type: none"> • XNT 9 DI T • XNT 9 28 T • XNT 9 HW T • XNT 9 20 T • XNT 9 20 • XNT 14 20 T • XNT 14 74 T • XNT 14 DI T


IN-DASH MOUNTS	Item Number	Description	Compatible Units
 <p data-bbox="261 344 399 373">IDMK H5</p>	740142-1	<p data-bbox="797 243 1057 436">In-dash mounting kit for quick and easy in-dash installation. Includes gasket, made of durable, adhesive backing</p>	<ul data-bbox="1084 268 1317 298" style="list-style-type: none"> • All HELIX 5 Series
 <p data-bbox="261 653 399 682">IDMK H7</p>	740174-1	<p data-bbox="797 518 1057 669">In-dash mounting kit for quick and easy in-dash installation. Includes bracket and hardware</p>	<ul data-bbox="1084 548 1308 577" style="list-style-type: none"> • All HELIX 7 Series
 <p data-bbox="240 890 415 919">IDMK H89R</p>	740179-1	<p data-bbox="797 735 1057 886">In-dash mounting kit for quick and easy in-dash installation. Includes bracket, clamp and hardware</p>	<ul data-bbox="1084 726 1484 785" style="list-style-type: none"> • HELIX 8 G3N Series - All models • HELIX 9 G3N Series - All models
 <p data-bbox="240 1136 415 1165">IDMK H910R</p>	740155-1	<p data-bbox="797 1010 1057 1161">In-dash mounting kit for quick and easy in-dash installation. Includes bracket, clamp and hardware</p>	<ul data-bbox="1084 1039 1455 1098" style="list-style-type: none"> • All HELIX 9 Series, except G3N models
 <p data-bbox="245 1451 415 1480">IDMK H12R</p>	740175-1	<p data-bbox="797 1289 1057 1440">In-dash mounting kit for quick and easy in-dash installation. Includes bracket, clamp and hardware</p>	<ul data-bbox="1084 1318 1321 1348" style="list-style-type: none"> • All HELIX 12 Series
 <p data-bbox="245 1772 415 1801">IDMK H15R</p>	740194-1	<p data-bbox="786 1556 1065 1707">In-dash mounting kit for quick and easy in-dash installation. Includes bracket, clamp and hardware</p>	<ul data-bbox="1084 1585 1326 1614" style="list-style-type: none"> • All HELIX 15 Series

 <p>IDMK S10</p>	740173-1	<p>In-dash mounting kit for quick and easy in-dash installation. Includes bracket and hardware</p>	<ul style="list-style-type: none"> • SOLIX 10 Series - All Models
 <p>IDMK S12</p>	740176-1	<p>In-dash mounting kit for quick and easy in-dash installation. Includes bracket and hardware</p>	<ul style="list-style-type: none"> • SOLIX 12 Series - All Models
 <p>IDMK S15</p>	740177-1	<p>In-dash mounting kit for quick and easy in-dash installation. Includes bracket and hardware</p>	<ul style="list-style-type: none"> • SOLIX 15 Series - All Models
 <p>IDMK RM A13</p>	740191-1	<p>The IDMK RM A13 is an in-dash mounting solution for APEX 13 models where a rear-mounted bracket solution is desired for installation.</p>	<ul style="list-style-type: none"> • All APEX 13 Series
 <p>IDMK RM A16</p>	740192-1	<p>The IDMK RM A16 is an in-dash mounting solution for APEX 16 models where a rear-mounted bracket solution is desired for installation.</p>	<ul style="list-style-type: none"> • All APEX 16 Series






 <p>IDMK RM A19</p>	740193-1	<p>The IDMK RM A19 is an in-dash mounting solution for APEX 19 models where a rear-mounted bracket solution is desired for installation.</p>	<ul style="list-style-type: none"> • All APEX 19 Series
 <p>IDMK FM APX</p>	740190-1	<p>The IDMK FM APX is a front in-dash mounting solution for APEX. This product provides a secure fit of the APEX control head to the mounting surface and is a replacement for the front in-dash mounting options that comes standard with APEX.</p>	<ul style="list-style-type: none"> • All APEX 13 / 16 / 19 models
MOUNTING HARDWARE			
MOUNTING HARDWARE	Item Number	Description	Compatible Units
 <p>GM S10</p>	740172-1	<p>Replacement Mounting Bracket Kit</p> <ul style="list-style-type: none"> • Includes attachment screws and knobs 	<ul style="list-style-type: none"> • SOLIX 10 Series - All Models
 <p>GM S12</p>	740164-1	<p>Replacement Mounting Bracket Kit</p> <ul style="list-style-type: none"> • Includes Attachment Screws and Knobs 	<ul style="list-style-type: none"> • SOLIX 12 Series - All Models
 <p>GM S15</p>	740165-1	<p>Replacement Mounting Bracket Kit</p> <ul style="list-style-type: none"> • Includes Attachment Screws and Knobs 	<ul style="list-style-type: none"> • SOLIX 15 Series - All Models
 <p>GM H5</p>	740143-1	<p>Replacement Mounting Bracket Kit includes attachment screws and knobs</p>	<ul style="list-style-type: none"> • All HELIX 5 Series


 <p>GM H7</p>	740146-1	Replacement Mounting Bracket Kit includes attachment screws and knobs	<ul style="list-style-type: none"> • All HELIX 7 Series
 <p>GM H910</p>	740149-1	Replacement Mounting Bracket Kit includes attachment screws and knobs	<ul style="list-style-type: none"> • All HELIX 8 Series • All HELIX 9 Series • All HELIX 10 Series
 <p>GM H12</p>	740151-1	Replacement Mounting Bracket Kit includes attachment screws and knobs	<ul style="list-style-type: none"> • All HELIX 12 Series
 <p>GM H15</p>	740194-1	Replacement Mounting Bracket Kit includes attachment screws and knobs	<ul style="list-style-type: none"> • All HELIX 15 Series
 <p>GM A13</p>	740186-1	Replacement Mounting Bracket Kit includes attachment screws and knobs	<ul style="list-style-type: none"> • All APEX 13 Series
 <p>GM A16</p>	740187-1	Replacement Mounting Bracket Kit includes attachment screws and knobs	<ul style="list-style-type: none"> • All APEX 16 Series
 <p>GM A19</p>	740188-1	Replacement Mounting Bracket Kit includes attachment screws and knobs	<ul style="list-style-type: none"> • All APEX 19 Series

TEMPERATURE AND SPEED SENSORS	Item Number	Description	Compatible Units
 <p data-bbox="282 436 373 470">TS W</p>	730000-1	Transom Mount Speed/ Temp sensor	<ul style="list-style-type: none"> • ONIX 10 - TS W+ PC 12 ST • ONIX 8 -TS W+ PC 12ST • SOLIX 12 TS W+ PC 12ST • SOLIX 15 TS W + PC 12 ST • 700 HD - TS W + AS TY • 600 Series TS W + ASTY • 500 Series, 800 Series, 900 Series, 1100 Series, • ALL HELIX Series
EXTENSION CABLES	Item Number	Description	Compatible Units
 <p data-bbox="269 915 383 949">EC M10</p>	720096-1	Transducer extension cable 10 Feet, 7 Pin style transducers	<ul style="list-style-type: none"> • All transducers except for those used with the following fish finders: APEX, SOLIX, ION, ONIX and Fishin' Buddy • Compatible Transducers: XNT 9 HW T, XNT 9 HW MDI 75 T, XM 9 HW MDI T, XNT 9 HW MSI 150 T, XM 9 HW MSI T, XP 9 H, XP 9 HW T, XTM 9 HW T, XTM 9 HW MDI 75 T, XTM 9 HW MDI T, XTM 9 HW MSI 150T, XTM 9 HW MSI T, XPT 9 HW T, XPTH 9 HW T, XPTH 9 HW MSI T, XNT 9 20 T, XNT 9 20, XNT 9 28 T, XNT 9 28, XP 9 20 T, XP 9 20, XAP 9 20, XTM 9 20 T, XTM 9 20, XHS 9 HDSI 180 T, XNT 9 180 T, XNT 9 QB 90 T, XNT 9 DB 74 T, XTM 9 QB 90 T, XM 9 20 MSI T, XTM 9 20 MSI T, XPTH 9 20 MSI T
 <p data-bbox="261 1583 378 1617">EC M30</p>	720096-2	Transducer extension cable 30 Feet, 7 Pin	<ul style="list-style-type: none"> • All transducers except for those used with the following fish finders: APEX, SOLIX, ION, ONIX and Fishin' Buddy • Compatible Transducers: XNT 9 HW T, XNT 9 HW MDI 75 T, XM 9 HW MDI T, XNT 9 HW MSI 150 T, XM 9 HW MSI T, XP 9 H, XP 9 HW T, XTM 9 HW T, XTM 9 HW MDI 75 T, XTM 9 HW MDI T, XTM 9 HW MSI 150T, XTM 9 HW MSI T, XPT 9 HW T, XPTH 9 HW T, XPTH 9 HW MSI T, XNT 9 20 T, XNT 9 20, XNT 9 28 T, XNT 9 28, XP 9 20 T, XP 9 20, XAP 9 20, XTM 9 20 T, XTM 9 20, XHS 9 HDSI 180 T, XNT 9 180 T, XNT 9 QB 90 T, XNT 9 DB 74 T, XTM 9 QB 90 T, XM 9 20 MSI T, XTM 9 20 MSI T, XPTH 9 20 MSI T


 <p>EC M3 14W10</p>	<p>720106-1</p>	<p>10' Extension Cable for 14-pin transducers</p>	<ul style="list-style-type: none"> • Compatible with transducers for the following models: <ul style="list-style-type: none"> -MEGA 360 Imaging -Built-in MEGA Imaging on select Minn Kota trolling motors - All 14-pin transducers; including: <ul style="list-style-type: none"> XNT 14 HW T, XM 14 HW MDI T, XM 14 HW MSI T, XP 14 HW, XP 14 HW T, XTM 14 HW T, XTM 14 HW MDI T, SSTH 14 HW MSI+ T, XPTH 14 HW T, XPTH 14 HW MSI T, XNT 14 20 T, XM 14 20 MSI T, XP 14 20 T, XTM 14 20 T, XPTH 14 20 MSI T 				
 <p>EC M3 14W30</p>	<p>720106-2</p>	<p>30' Extension Cable for 14-pin transducers</p>	<ul style="list-style-type: none"> • Compatible with transducers for the following models: <ul style="list-style-type: none"> -MEGA 360 Imaging -Built-in MEGA Imaging on select Minn Kota trolling motors - All 14-pin transducers; including: <ul style="list-style-type: none"> XNT 14 HW T, XM 14 HW MDI T, XM 14 HW MSI T, XP 14 HW, XP 14 HW T, XTM 14 HW T, XTM 14 HW MDI T, SSTH 14 HW MSI+ T, XPTH 14 HW T, XPTH 14 HW MSI T, XNT 14 20 T, XM 14 20 MSI T, XP 14 20 T, XTM 14 20 T, XPTH 14 20 MSI T 				
<table border="1"> <thead> <tr> <th data-bbox="90 1297 553 1377">POWER CABLES</th> <th data-bbox="553 1297 776 1377">Item Number</th> <th data-bbox="776 1297 1073 1377">Description</th> <th data-bbox="1073 1297 1534 1377">Compatible Units</th> </tr> </thead> </table>				POWER CABLES	Item Number	Description	Compatible Units
POWER CABLES	Item Number	Description	Compatible Units				
 <p>HCCT</p>	<p>740184-1</p>	<p>HELIX Cable Connector Tray Connect multiple cable inputs with a single tray Simple installation for quick removal, storage and security</p>	<ul style="list-style-type: none"> • HELIX 8 - All models • HELIX 9 - All models • HELIX 10 - All models • HELIX 12 - All models • HELIX 15 - All models 				


 <p>PC 10</p>	720002-1	Power cable - 6 feet long	<ul style="list-style-type: none"> • Many Humminbird models produced after 1988; including • 300, 500, 700 Series (non-Side or Down Imaging models) • HELIX 5 & 7 Series (non-Side or Down Imaging models) • PMAX Series
 <p>PC 11</p>	720057-1	Power cable w/choke- 6 feet long	<ul style="list-style-type: none"> • All 700 HD, 800, 900, 1100 Series models • All HELIX 5 and 7 Side Imaging and Down Imaging models • All HELIX 8 / 9 / 10 / 12 / 15 Series
 <p>PC HELIX 12V DC</p>	720105-1	12V Cigarette Lighter power cord, 8 ft long	<ul style="list-style-type: none"> • All HELIX models • All ICE HELIX models • All ICE Flashers models • All 300, 500, 700, 800, 900, 1100 models
 <p>PC 12</p>	720085-1	Power cable- 6 feet in length	<ul style="list-style-type: none"> • All SOLIX Series • All ONIX Series
 <p>PC 13</p>	720110-1	Power cable- 10 feet in length	<ul style="list-style-type: none"> • All APEX Series
 <p>PC MEGA 360</p>	720118-1	MEGA 360 Imaging power cable (boat side). Must be used in connection with MEGA 360 Imaging transducer and built-in power connector. 10 feet long	<ul style="list-style-type: none"> • All MEGA 360 Imaging models


TRANSDUCER ADAPTER CABLES	Item Number	Description	Compatible Units
 <p>9 M SIDB Y</p>	720101-1	<p>Transducer Y-cable allows both a Side Imaging and a 2D transducer to be connected to one Humminbird unit for high speed depth and sonar performance.</p>	<ul style="list-style-type: none"> • All Side Imaging and Down Imaging units in the following series: 300, 500, 700, 800, 900, 1100, HELIX series *Compatible with models that utilize 455kHz/800kHz, MEGA Imaging and MEGA Imaging+ frequencies
 <p>9 M SILR Y</p>	720102-1	<p>Y-cable allows for installation of separate left and right Side Imaging transducers to be connected to one Humminbird unit for a combined Side Imaging picture</p>	<ul style="list-style-type: none"> • All Side Imaging and Down Imaging units in the following series: 300, 500, 700, 800, 900, 1100, HELIX series *Compatible with models that utilize 455kHz/800kHz, MEGA Imaging and MEGA Imaging+ frequencies
 <p>14 M ID SIDB Y</p>	720111-1	<p>Transducer Y-cable allows both a Side Imaging and a 2D transducer to be connected to one Humminbird unit for high speed depth and sonar performance. Supports Airmar Transducer ID.</p>	<ul style="list-style-type: none"> • APEX Series <ul style="list-style-type: none"> - All models • SOLIX Series <ul style="list-style-type: none"> - All models
 <p>14 M ID SILR Y</p>	720112-1	<p>Y-cable allows for installation of separate left and right Side Imaging transducers to be connected to one Humminbird unit for a combined Side Imaging picture. Supports Airmar Transducer ID.</p>	<ul style="list-style-type: none"> • APEX Series <ul style="list-style-type: none"> - All models • SOLIX Series <ul style="list-style-type: none"> - All models
 <p>9 M360 2DDI Y</p>	720107-1	<p>Combines MEGA 360 Imaging transducer and 7-pin Dual Spectrum/MEGA Imaging+ transducers into one 7-pin transducer plug for connection to the same, compatible HELIX fish finder.</p>	<ul style="list-style-type: none"> • HELIX G3N models with MEGA Imaging+ • For use when connecting a MEGA 360 Imaging transducer to a single compatible HELIX fish finder, in conjunction with an external transducer (Dual Spectrum CHIRP or DI & Dual Spectrum CHIRP transducer)

 <p>14 M360 2DDI Y</p>	720108-1	Combines MEGA 360 Imaging transducer and 14-pin Dual Spectrum / MEGA Imaging+ transducers (including Built-in MEGA Imaging) into one 14-pin plug for connection to the same, compatible control head. 30" on Dual Spectrum CHIRP side of cable and 10' cable on the MEGA 360 side	<ul style="list-style-type: none"> • All SOLIX 10/12/15 G2 models • For use when connecting a MEGA 360 Imaging transducer to a compatible SOLIX or HELIX fish finder, in conjunction with a Built-in MEGA Imaging transducer or external 14-pin 2D /MDI transducer.
---	----------	---	---




ETHERNET CABLES	Item Number	Description	Compatible Units
-----------------	-------------	-------------	------------------

 <p>AC EC 5E</p>	720073-6	Ethernet Cable – 5ft Female-Female: *May require use of AS EC QDE depending on Compatible unit. See AS EC QDE for details	<ul style="list-style-type: none"> • All APEX, SOLIX, ION, ONIX <p>The below models also require (1) AS EC QDE to use this product:</p> <ul style="list-style-type: none"> • 1199ci HD SI, 1159ci HD DI, 1159ci HD • 999ci HD, 959ci HD DI, 959ci HD • 899ci HD, 859ci HD DI, 859ci HD • 798ci HD • HELIX 9, 10, 12 Gen-1 models • All HELIX G2N and newer models
---	----------	---	--




 <p>AS EC 10E</p>	720073-2	Ethernet Cable – 10 ft Female-Female: *May require use of AS EC QDE depending on Compatible unit. See AS EC QDE for details	<ul style="list-style-type: none"> • All APEX, SOLIX, ION, ONIX <p>The below models also require (1) AS EC QDE to use this product:</p> <ul style="list-style-type: none"> • 1199ci HD SI, 1159ci HD DI, 1159ci HD • 999ci HD, 959ci HD DI, 959ci HD • 899ci HD, 859ci HD DI, 859ci HD • 798ci HD • HELIX 9, 10, 12 Gen-1 models • All HELIX G2N and newer models
--	----------	---	--

 <p>AS EC 15E</p>	720073-5	Ethernet Cable - 15 ft Female-Female: *May require use of AS EC QDE depending on Compatible unit. See AS EC QDE for details	<ul style="list-style-type: none"> • All APEX, SOLIX, ION, ONIX <p>The below models also require (1) AS EC QDE to use this product:</p> <ul style="list-style-type: none"> • 1199ci HD SI, 1159ci HD DI, 1159ci HD • 999ci HD, 959ci HD DI, 959ci HD • 899ci HD, 859ci HD DI, 859ci HD • 798ci HD • HELIX 9, 10, 12 Gen-1 models • All HELIX G2N and newer models
--	----------	---	--


 <p>AS EC 20E</p>	<p>720073-3</p>	<p>Ethernet Cable – 20 ft Female-Female:</p> <p>*May require use of AS EC QDE depending on Compatible unit.</p> <p>See AS EC QDE for details</p>	<ul style="list-style-type: none"> • All APEX, SOLIX, ION, ONIX <p>The below models also require (1) AS EC QDE to use this product:</p> <ul style="list-style-type: none"> • 1199ci HD SI, 1159ci HD DI, 1159ci HD • 999ci HD, 959ci HD DI, 959ci HD • 899ci HD, 859ci HD DI, 859ci HD • 798ci HD • HELIX 9, 10, 12 Gen-1 models • All HELIX G2N and newer models
 <p>AS EC 30E</p>	<p>720073-4</p>	<p>Ethernet Cable - 30 ft Female-Female:</p> <p>*May require use of AS EC QDE depending on Compatible unit.</p> <p>See AS EC QDE for details</p>	<ul style="list-style-type: none"> • All APEX, SOLIX, ION, ONIX <p>The below models also require (1) AS EC QDE to use this product:</p> <ul style="list-style-type: none"> • 1199ci HD SI, 1159ci HD DI, 1159ci HD • 999ci HD, 959ci HD DI, 959ci HD • 899ci HD, 859ci HD DI, 859ci HD • 798ci HD • HELIX 9, 10, 12 Gen-1 models • All HELIX G2N and newer models
 <p>AS ECX 30E</p>	<p>760025-1</p>	<p>Ethernet Extension Cable Female-Male:</p> <p>The Ethernet Extension Cable is a 30' cable that allows you to extend the length of your ethernet cables.</p>	<p>Requires at least one Ethernet cable: AS EC5E AS EC10E, AS EC15E, AS EC20E, AS EC30E</p> <ul style="list-style-type: none"> • All APEX, SOLIX, ION, ONIX <p>These models also require (1) AS EC QDE to use this product:</p> <ul style="list-style-type: none"> • 1199ci HD SI, 1159ci HD DI, 1159ci HD • 999ci HD, 959ci HD DI, 959ci HD • 899ci HD, 859ci HD DI, 859ci HD • 798ci HD • HELIX 9, 10, 12 Gen-1 models • All HELIX G2N and newer models
 <p>AS EC QDE</p>	<p>720074-1</p>	<p>Ethernet Adapter Cable converts from metal screw-on connector quick-disconnect, press-fit connector.</p>	<ul style="list-style-type: none"> • The below models also require (1) AS EC QDE to connect to complete an Ethernet connection: • 1199ci HD SI, 1159ci HD DI, 1159ci HD • 999ci HD, 959ci HD DI, 959ci HD • 899ci HD, 859ci HD DI, 859ci HD • 798ci HD • HELIX 9, 10, 12 Gen-1 models • All HELIX G2N and newer models

 <p>AS ETH 5PXG</p>	<p>408450-1</p>	<p>Use this 5-Port Ethernet Switch to network multiple Humminbird units, radar, Minn Kota trolling motors. Ethernet cable(s) are required depending on the number of devices you plan to add to this switch.</p>	<ul style="list-style-type: none"> • All APEX, SOLIX, ION, ONIX <p>The below models also require (1) AS EC QDE to use this item:</p> <ul style="list-style-type: none"> • 1199ci HD SI, 1159ci HD DI, 1159ci HD • 999ci HD, 959ci HD DI, 959ci HD • 899ci HD, 859ci HD DI, 859ci HD • 798ci HD, 788ci HD DI, 788ci HD • HELIX 9, 10, 12 Gen-1 models • All HELIX G2N and newer models
 <p>DUAL HELIX STARTER KIT HWAL MI</p>	<p>760062-1</p>	<p>Everything needed to network two Ethernet-equipped, HELIX models on your aluminum boat. (1) XNT 9 HW T Transom Mount Dual Spectrum HW CHIRP Transducer and metal mounting hardware, (1) AS EC 20E Ethernet Cable, (2) AS EC QDE Ethernet Adapters, (1) MKR-MI-1 Built-In MEGA Imaging Trolling Motor Adapter, (1) 9 M SIDB Y Transducer Y-Cable</p>	<ul style="list-style-type: none"> • HELIX 8 / 9 / 10 / 12 / 15 Series - G3N / G4N models
 <p>DUAL HELIX STARTER KIT HWFG MI</p>	<p>760063-1</p>	<p>Everything needed to network two Ethernet-equipped, HELIX models on your fiberglass boat. (1) XP 9 HW T In-Hull Mount Dual Spectrum HW CHIRP Transducer and epoxy, (1) AS EC 20E Ethernet Cable, (2) AS EC QDE Ethernet Adapters, (1) MKR-MI-1 Built-In MEGA Imaging Trolling Motor Adapter, (1) 9 M SIDB Y Transducer Y-Cable.</p>	<ul style="list-style-type: none"> • HELIX 8 / 9 / 10 / 12 / 15 Series - G3N / G4N models

MEGA 360 IMAGING	Item Number	Description	Compatible Units
 <p data-bbox="138 703 527 745">MEGA 360 Imaging-Ultrex</p>	411250-1	<p data-bbox="787 178 1063 367">MEGA 360 Imaging transducer, compatible with ULTREX trolling motors, provides 125' of MEGA Imaging detail all around your boat.</p> <p data-bbox="820 409 1031 472"><u>RECOMMENDED ACCESSORIES:</u></p> <p data-bbox="803 472 1047 535">HELIX: • AS GPS HS (Part# 408400-1)</p> <p data-bbox="803 535 1047 598">SOLIX: • AS GPS HS (Part#408400-1)</p> <p data-bbox="820 598 1031 661">• AS GPS NMEA (Part# 720080-1)</p> <p data-bbox="803 661 1047 703">Transducer Y Cable:</p> <p data-bbox="820 703 1031 766">• 14 M360 2DDI Y (Part# 720108-1)</p> <p data-bbox="901 766 950 798">OR</p> <p data-bbox="868 798 1063 861">• 9 M360 2DDI Y (Part# 720107-1)</p>	<ul data-bbox="1088 210 1526 430" style="list-style-type: none"> • All HELIX 8-15 G3N / G4N models with MEGA Imaging+ • All SOLIX G2/G3 models • All APEX models • Designed for use with MINN KOTA® Ultrex trolling motors
 <p data-bbox="97 1333 544 1375">MEGA 360 Imaging – Fortrex</p>	411260-1	<p data-bbox="787 945 1063 1176">MEGA 360 Imaging transducer, compatible with FORTREX and MAXXUM trolling motors, provides 125' of MEGA Imaging detail all around your boat.</p> <p data-bbox="820 1207 1031 1270"><u>RECOMMENDED ACCESSORIES:</u></p> <p data-bbox="803 1270 1047 1333">HELIX: • AS GPS HS (Part# 408400-1)</p> <p data-bbox="803 1333 1047 1396">SOLIX: • AS GPS HS (Part#408400-1)</p> <p data-bbox="820 1396 1031 1459">• AS GPS NMEA (Part# 720080-1)</p> <p data-bbox="803 1459 1047 1501">Transducer Y Cable:</p> <p data-bbox="820 1501 1031 1564">• 14 M360 2DDI Y (Part# 720108-1)</p> <p data-bbox="901 1564 950 1596">OR</p> <p data-bbox="820 1596 1015 1659">• 9 M360 2DDI Y (Part# 720107-1)</p>	<ul data-bbox="1088 955 1526 1165" style="list-style-type: none"> • All HELIX 8-15 G3N / G4N models with MEGA Imaging+ • All SOLIX G2/G3 models • All APEX models • Designed for use with MINN KOTA® Fortrex and Maxxum Trolling Motors

 <p>MEGA 360 Imaging - Universal</p>	<p>411390-1</p>	<p>MEGA 360 Imaging transducer, with universal boat mount, provides 125' of MEGA Imaging detail all around your boat.</p> <p><u>RECOMMENDED ACCESSORIES:</u> HELIX: • AS GPS HS (Part# 408400-1) SOLIX: • AS GPS HS (Part#408400-1) • AS GPS NMEA (Part# 720080-1) Transducer Y Cable: • 14 M360 2DDI Y (Part# 720108-1) OR • 9 M360 2DDI Y (Part# 720107-1)</p>	<ul style="list-style-type: none"> • All HELIX 8-15 G3N / G4N models with MEGA Imaging+ • All SOLIX G2/G3 models • All APEX models • Universal mount is configurable to almost any boat with adjustable GiegerTec Marine mount.
 <p>MEGA 360 Imaging – No Mount</p>	<p>411580-1</p>	<p>MEGA 360 Imaging transducer without mount. Will need an accessory mount (not included) to use this product</p> <p><u>RECOMMENDED ACCESSORIES:</u> HELIX: • AS GPS HS (Part# 408400-1) SOLIX: • AS GPS HS (Part#408400-1) • AS GPS NMEA (Part# 720080-1) Transducer Y Cable: • 14 M360 2DDI Y (Part# 720108-1) OR • 9 M360 2DDI Y (Part# 720107-1)</p>	<ul style="list-style-type: none"> • All HELIX 8-15 G3N / G4N models with MEGA Imaging+ • All SOLIX G2 models with MEGA Imaging+ • All APEX models • Universal mount is configurable to almost any boat with adjustable GiegerTec Marine mount.
 <p>AD Ultrex MEGA 360 Hardware Kit</p>	<p>740171-1</p>	<p>The Ultrex MEGA 360 Hardware Kit provides the components needed to mount a MEGA 360 Imaging accessory transducer on a Minn Kota Ultrex™ bow-mount trolling motor.</p>	<p>Compatible with: MEGA 360 Imaging – Ultrex MEGA 360 Imaging – Universal MEGA 360 Imaging – No Mount</p>

 <p>MEGA 360 Ice Adapter</p>	740198-1	<p>The MEGA 360 Ice Adapter includes all the components needed to convert a MEGA 360 Imaging transducer for use while ice fishing.</p>	<p>Compatible with: MEGA 360 Imaging – Ultrex MEGA 360 Imaging – Fortrex MEGA 360 Imaging – Universal MEGA 360 Imaging – No Mount</p>
MEGA Live Imaging	Item Number	Description	Compatible Units
 <p>MEGA Live Imaging – Shaft Mount</p>	710304-1	<p>MEGA Live Imaging provides the most impressive live sonar on the water, allowing you to watch fish and structure in real-time, powered by the unmatched detail of MEGA Imaging®</p>	<ul style="list-style-type: none"> • All APEX models • All SOLIX models • HELIX 8-15 G3N / G4N models with MEGA Imaging
ADVANCED FISHING SYSTEMS	Item Number	Description	Compatible Units
 <p>AS ETH NMEA2K</p>	408390-1	<p>Waterproof black box, connects via Ethernet Connects to established NMEA 2000® network. Intuitive user interface features data boxes and pre-programmed instrument views</p>	<p>These models also require (1) AS EC QDE to use this product:</p> <ul style="list-style-type: none"> • 1199ci HD SI, 1159ci HD DI, 1159ci HD • 999ci HD, 959ci HD DI, 959ci HD • 899ci HD, 859ci HD DI, 859ci HD • 798ci HD • HELIX 9, 10, 12 Gen-1 models • All HELIX G2N and G3N models
 <p>AS QD NMEA 2000</p>	720114-1	<p>Quick-disconnect cable to convert NMEA 2000® drop cable for connection with HELIX models.</p>	<ul style="list-style-type: none"> • HELIX 8 / 9 / 10 / 12 / 15 Series - G4N models

 <p>AS NMEA</p>	720116-1	<p>The AS NMEA is an adapter cable that allows APEX chartplotters to connect directly with a NMEA 0183 accessory (sold separately). The AS NMEA measures 40" in length and connects to the MFD via a waterproof connector.</p>	<ul style="list-style-type: none"> • APEX 13/16/19 Series - All models
 <p>NMEA 2000 Starter Kit- Single</p>	760064-1	<p>The NMEA 2000 Starter Kit - Single provides the essential components to build a single device NMEA 2000 network.</p>	<ul style="list-style-type: none"> • Compatible with all NMEA 200 accessories
 <p>NMEA 2000 Starter Kit- Dual</p>	760065-1	<p>The NMEA 2000 Starter Kit - Dual provides the essential components to build a dual device NMEA 2000 network.</p>	<ul style="list-style-type: none"> • Compatible with all NMEA 200 accessories
 <p>NMEA 2000 Terminator - Female</p>	760035-1	<p>This NMEA 2000 terminator (FEMALE) allows for proper termination of an NMEA 2000 network. The couplers connect to the corresponding T-connectors for a simple installation.</p>	<ul style="list-style-type: none"> • Compatible with all NMEA 200 accessories
 <p>NMEA 2000 Terminator - Male</p>	760036-1	<p>This NMEA 2000 terminator (MALE) allows for proper termination of an NMEA 2000 network. The couplers connect to the corresponding T-connectors for a simple installation.</p>	<ul style="list-style-type: none"> • Compatible with all NMEA 200 accessories

 <p>NMEA 2000 POWER T</p>	<p>760037-1</p>	<p>This NMEA 2000 power cable with T-connector allows for power connection to an NMEA 2000 network quickly and easily.</p>	<ul style="list-style-type: none"> • Compatible with all NMEA 200 accessories
 <p>NMEA 2000 T-CONNECTOR</p>	<p>760038-1</p>	<p>This NMEA 2000 T-connector offers connection between a NMEA 2000 drop cable and backbone connections.</p>	<ul style="list-style-type: none"> • Compatible with all NMEA 200 accessories
 <p>NMEA 2000 DROP CABLE 0.5M</p>	<p>720117-1</p>	<p>This 0.5 meter NMEA 2000 drop cable offers connection between a NMEA 2000 device and T-connector. The couplers connect to the corresponding T-connectors, creating a simplified installation.</p>	<ul style="list-style-type: none"> • Compatible with all NMEA 200 accessories
 <p>NMEA 2000 DROP CABLE 2M</p>	<p>720117-2</p>	<p>This 2 meter NMEA 2000 drop cable offers connection between a NMEA 2000 device and T-connector. The couplers connect to the corresponding T-connectors, creating a simplified installation.</p>	<ul style="list-style-type: none"> • Compatible with all NMEA 200 accessories
 <p>NMEA 2000 DROP CABLE 5M</p>	<p>720117-3</p>	<p>This 5 meter NMEA 2000 drop cable offers connection between a NMEA 2000 device and T-connector. The couplers connect to the corresponding T-connectors, creating a simplified installation.</p>	<ul style="list-style-type: none"> • Compatible with all NMEA 200 accessories





 <p>NMEA 2000 DROP CABLE 10M</p>	720117-4	<p>This 10 meter NMEA 2000 drop cable offers connection between a NMEA 2000 device and T-connector. The couplers connect to the corresponding T-connectors, creating a simplified installation.</p>	<ul style="list-style-type: none"> • Compatible with all NMEA 200 accessories
 <p>AS HHGPS</p>	700030-1	<p>Handheld GPS Connection Kit includes: NMEA connection cable, Y cable and detailed instructions. This kit requires the handheld GPS manufacturers NMEA data cable to complete the connection to your handheld GPS.</p>	<ul style="list-style-type: none"> • All 700 Series • All 800 Series • All 900 Series • All 1100 Series
 <p>AS T Y</p>	720075-1	<p>This Y cable is required for optional temp sensor to connect to Select Humminbird Series product.</p>	<ul style="list-style-type: none"> • 600 series • 700 series • 800 series • 900 series • 1100 series • All HELIX models
 <p>AS GPS NMEA</p>	720080-1	<p>Adapter Cable to connect with optional external GPS receiver AS GRP or AS GPS HS and 1 additional NMEA 0183 communication</p>	<ul style="list-style-type: none"> • All SOLIX Series • All ONIX Series
 <p>AS GPS</p>	720113-1	<p>The AS GPS is an adapter cable that allows APEX chartplotters to connect with a Humminbird external GPS receiver (AS GRP or AS GPS HS) [sold separately]. Cable measures 30" in length.</p>	<ul style="list-style-type: none"> • APEX 13/16/19 Series - All models

 <p>AS GRP</p>	<p>408920-1</p>	<p>Precision GPS/WAAS receiver provides fast position fixes accurate within 2.5 meters.</p>	<ul style="list-style-type: none"> • All HELIX 7 G2N/G3N Series • All HELIX 8 / 9 / 10 / 12 / 15 Series models <p>Models require (1) AS GPS NMEA</p> <ul style="list-style-type: none"> • All ONIX Series • All SOLIX Series <p>Models require (1) AS GPS</p> <ul style="list-style-type: none"> • All APEX Series
 <p>AS GPS HS</p>	<p>408400-1</p>	<p>Precision GPS/WAAS receiver provides fast position fixes accurate within 2.5 meters and provides constant vessel heading with internal heading sensor compass</p>	<ul style="list-style-type: none"> • All HELIX 7 G2N/G3N Series • All HELIX 8 / 9 / 10 / 12 / 15 Series models • 859ci HD Combo, 859ci HD DI Combo, 859ci HD XD Combo, 899ci HD SI Combo • 959ci HD Combo, 959ci HD DI Combo, 959ci HD XD Combo, 999ci HD SI Combo • 1159ci HD Combo, 1159ci HDDI Combo, 1159ci HD XD Combo, 1199ci HD SI Combo <p>Models require (1) AS GPS NMEA</p> <ul style="list-style-type: none"> • All ONIX Series • All SOLIX Series <p>Models require (1) AS GPS</p> <ul style="list-style-type: none"> • All APEX Series
 <p>AD HDMI 10</p>	<p>720115-1</p>	<p>The AD HDMI 10 is a marine-rated HDMI cable for connecting APEX chartplotters to video and camera inputs or connecting APEX to an HDMI accessory display. Measures 10 feet in length.</p>	<ul style="list-style-type: none"> • APEX 13/16/19 Series - All models
UNIT COVERS	Item Number	Description	Compatible Units
 <p>UCPM 4</p>	<p>780033-1</p>	<p>Protective Cover protects lens during storage</p>	<ul style="list-style-type: none"> • PiranhaMAX 4 • PiranhaMAX 4 DI • Fishin Buddy MAX • Fishin Buddy MAX DI



 <p>UC H5</p>	780028-1	<p>Protective cover protects lens during storage. Durable, easy-on neoprene design</p>	<ul style="list-style-type: none"> • All HELIX 5 Series
 <p>UC H7</p>	780029-1	<p>Neoprene protective cover protects screen during storage. Durable, easy-on design</p>	<ul style="list-style-type: none"> • All HELIX 7 Series
 <p>UC H7 PR</p>	780036-1	<p>Protective cover protects screen during storage. Durable, easy-on rubberized design</p>	<ul style="list-style-type: none"> • HELIX 7 - all models
 <p>UC H89</p>	780038-1	<p>Protective cover protects screen during storage. Durable, easy-on rubberized design</p>	<ul style="list-style-type: none"> • HELIX 8 G3N models • HELIX 9 G3N models
 <p>UC H910</p>	780030-1	<p>Protective cover protects screen during storage. Durable, easy-on rubberized design</p>	<ul style="list-style-type: none"> • HELIX 9 Series <ul style="list-style-type: none"> ◦ Gen-1 and G2N models • All Helix 10 Series
 <p>UC H12</p>	780031-1	<p>Protective cover protects screen during storage. Durable, easy-on rubberized design</p>	<ul style="list-style-type: none"> • All HELIX 12 Series

 <p>UC H15</p>	780042-1	<p>Protective cover protects screen during storage. Durable, easy-on rubberized design</p>	<ul style="list-style-type: none"> • All HELIX 15 Series
 <p>UC S10</p>	780037-1	<p>Protective cover protects screen during storage. Durable, easy-on rubberized design</p>	<ul style="list-style-type: none"> • All SOLIX 10 Series
 <p>UC S12</p>	780034-1	<p>Protective cover protects lens during storage. Durable, easy-on rubberized design</p>	<ul style="list-style-type: none"> • All SOLIX 12 Series
 <p>UC S15</p>	780035-1	<p>Protective cover protects lens during storage. Durable, easy-on rubberized design</p>	<ul style="list-style-type: none"> • All SOLIX 15 Series
 <p>UC A13</p>	780039-1	<p>Protective cover protects lens during storage. Durable, easy-on rubberized design</p>	<ul style="list-style-type: none"> • All SOLIX 15 Series
 <p>UC A16</p>	780040-1	<p>Protective cover protects lens during storage. Durable, easy-on rubberized design</p>	<ul style="list-style-type: none"> • All SOLIX 15 Series
 <p>UC A19</p>	780041-1	<p>Protective cover protects lens during storage. Durable, easy-on rubberized design</p>	<ul style="list-style-type: none"> • All APEX 19 Series

PORTABLE CONFIGURATIONS	Item Number	Description	Compatible Units
 <p>9AH BK</p>	770030-1	Portable 9 Ah Battery and Charger	<ul style="list-style-type: none"> • All ICE Series • All HELIX Series • PiranhaMAX Series • 300 Series • 500 Series • 600 Series • 700 Series
 <p>PTC U2</p>	740157-1	Soft Portable Case (includes gel-cell battery and charger)	<ul style="list-style-type: none"> • All 100 Series • All 300 Series • All 500 Series • All 600 Series • All 700 Series • HELIX 5 Series • HELIX 7 Series
 <p>PTC UNB2</p>	740157-1NB	Soft Portable Case without battery (unit not included)	<ul style="list-style-type: none"> • All 100 Series • All 300 Series • All 500 Series • All 600 Series • All 700 Series • HELIX 5 Series • HELIX 7 Series
ICE ACCESSORIES	Item Number	Description	Compatible Units
 <p>ICE PTC CHIRP H57 FB</p>	740178-1NB	ICE conversion kit for HELIX CHIRP models. Includes Dual Spectrum CHIRP Ice transducer / float, mounting hardware, soft side bag and power cable. Battery and charger NOT included	<ul style="list-style-type: none"> • All HELIX 5 G2 & HELIX 7 G2, G2N, G3 and G3N models with CHIRP • All ICE HELIX G2/G2N/G3/G3N Series models
 <p>ICE PTC CHIRP H8910</p>	740185-NB	ICE conversion kit for HELIX CHIRP models. Includes Dual Spectrum CHIRP Ice transducer / float, mounting hardware, and power cable. Battery and charger NOT included	<ul style="list-style-type: none"> • All HELIX 8 / 9 / 10 models with CHIRP sonar <ul style="list-style-type: none"> ◦ G2N/G3N/G4N series

 <p>ICE PTC UNB2</p>	740158-1NB	ICE conversion kit for HELIX models without CHIRP sonar. Includes Dual Beam ice transducer / float, mounting hardware, soft side bag and power cable. Battery and charger NOT included.	<ul style="list-style-type: none"> • HELIX 5 SONAR • HELIX 5 SONAR GPS • HELIX 5 SONAR G2 • HELIX 7 SONAR • HELIX 7 SONAR GPS • HELIX 7 SONAR G2
 <p>MHX ICE</p>	740105-1	Mounting Hardware – Ice transducer and cable wrap	<ul style="list-style-type: none"> • ICE HELIX – All models
 <p>CC ICE</p>	780015-1	Soft Sided Bag for ICE Flashers	<ul style="list-style-type: none"> • ICE 35, ICE 45, ICE 55
<p>AUTOPILOT AND ACCESSORIES</p>	<p>Item Number</p>	<p>Description</p>	<p>Compatible Units</p>
 <p>SC 110 AP Kit</p>	700052-1	Kit includes Autopilot 3.5" color TFT display, Course Computer with Fluxgate Compass, Rudder Reedback Unit and Rate Gyro with 30m cable. Rotary knob and push button controls.	All Autopilot products are stand alone. They do not need a HB product to work
 <p>SC 110 AP Kit w/o FB</p>	700053-1	Kit includes Autopilot 3.5" color TFT display, Course Computer with Fluxgate Compass and Rate Gyro, and 30m cable. Rotary knob and push button controls.	All Autopilot products are stand alone. They do not need a HB product to work

 SC 110, display only	409100-1	3.5" color TFT display with rotary knob and push button controls.	<ul style="list-style-type: none"> • SC 110 AP Kit w/o FB
 SCP 110 Course Computer	408180-1	High speed, highly reliable SCP 110 course computer. It optimizes rudder movement by working with the GPS speed, Fluxgate Compass and Rate Gyro	<ul style="list-style-type: none"> • SC 110 AP Kit • SC 110 AP Kit w/o FB • SC 110 Display Only
 FB 30	408150-1	This brushless RFU features a unique, linear variable transformer - proving decades of reliable performance	<ul style="list-style-type: none"> • SC 110 AP Kit • SC 110 AP Kit w/o FB • SC 110 Display Only
 FXC 110	408210-1	This reliable electronic compass maintains your course based on magnetic heading reference. Automatic Self-Compensation, Ensures Relevant Magnetic Reference, Durable Construction	<ul style="list-style-type: none"> • SC 110 AP Kit • SC 110 AP Kit w/o FB • SC 110 Display Only
 HHRP 11-12	408340-1	Built with the finest components, Humminbird & reg pumps feature a full range of flow rates, pressure ratings and oil tank capacities. 1.0 cubic in per second, 12 VDC	<ul style="list-style-type: none"> • SC 110 AP Kit • SC 110 AP Kit w/o FB • SC 110 Display Only
 HHRP 17-12	408350-1	Built with the finest components, Humminbird & reg pumps feature a full range of flow rates, pressure ratings and oil tank capacities. 1.6 cubic in per second, 12 VDC	<ul style="list-style-type: none"> • SC 110 AP Kit • SC 110 AP Kit w/o FB • SC 110 Display Only

 <p>SCP Cable 30</p>	<p>720077-1</p>	<p>30 meter cable for the FB 30 and FXC 110 (included in Autopilot Kit SKU)</p>	<ul style="list-style-type: none"> • SC 110 AP Kit • SC 110 AP Kit w/o FB • SC 110 Display Only • FB 30 • FXC 110
RADAR	Item Number	Description	Compatible Units
 <p>HB2124</p>	<p>750013-1</p>	<p>Humminbird CHIRP Radar features CHIRP pulse compression. It delivers superior RADAR imaging on both long and extremely short ranges. This translates to better situational awareness in low-visibility conditions and helps identify birds and floating obstacles for clues to where gamefish are located. Track weather and vessels with amazing definition.</p>	<ul style="list-style-type: none"> • All HELIX 7 G2N/G3N models • All HELIX 8 Series • All HELIX 9 Series • All HELIX 10 Series • All HELIX 12 Series • All HELIX 15 Series • All ION Series • All ONIX Series • All SOLIX Series • All APEX Series