KICKER



KXMA-SERIES MARINE STEREO & 4-CHANNEL AMPS

Conformal-Coated Circuit Boards to Repel Moisture



Small Footprint to Tuck Out of the Way

316L Stainless-Steel, No-Rust Hardware 0-6dB Variable Bass Boost I



Marine-Compliant Terminals



Built-In Variable Crossovers for Precise Speaker Performance Matching

WHAT MAKES IT SUPERIOR?

- -Designed to Add Extra Intensity to a Large System, or Power High-End Tower Speakers
- -Marine-Environment-Ready
- -Highly Efficient Class D Technology
- -Superior Sound Quality and Added Power

Model	KXMA500.4	KXMA800.4	KXMA400.2	KXMA1200.2
Power [watts/ch] 2 Ohm Stereo:	125x4	200x4	200x2	600x2
Power [watts/ch] 4 Ohm Stereo:	75x4	100x4	100x2	300x2
Power [watts/ch] 4 Ohm Bridged Mono:	250x2	400×2	400x1	-
Dynamic Power [watts]	700	1100	500	1500
Frequency Response [Hz]:	10-20k	10-20k	10-20k	10-20k

KXMA.4 Crossover: OFF/HP/LP [amp 1], variable 10-5kHz w/ 10x switch; OFF/HP/LP/BP [amp 2], variable HP

10-500Hz; variable LP 40-5kHz w/ 10x switch; 24dB/octave

KXMA.2 Crossover: OFF/variable HP 10-500Hz/variable LP 40-500Hz (400-5kHz w/ 10x switch); BP capable

KXMA.4 KickEQ™ Bass Boost: variable 0-6dB @ 40Hz [amp 1 and 2]

KXMA.2 KickEQ™ Bass Boost: variable 0-6dB @ 40Hz

All Models DIMs [in, cm]: H - 2-1/8, 5.5; W - 8-5/16, 21

Length [in, cm]: 11-3/16, 28.4 11-9/16, 29.4 9-9/16, 24.4 11-3/16, 28.4

FOR MORE INFO: www.kicker.com/kxma-amplifiers



