



Sail cleats range

- Semi-flexible sides make it easy to fit to the sail.
- Adjust from either side of the sail.
- Smooth profile - snag free.
- Strong and impact resistant.
- Nylon or Alloy cleats available.

Full size image



1-4 mm Ø
(3/64" - 5/32")



CL273



CL273AN


CL269 Sail Edge cleat

All Nylon cleat.


Ideal for lower load applications.

CL267 Racing Sail Edge cleat

Racing Sail Line cleats




Easy fitting on the leech




Nylon casing for easy fitting and impact resistance.

CL267

Alloy cleat for strength and long life.




Rivet



Sew


NEW

CL273 Starboard



ORIGINAL

CL241 Port



The range of Sail cleats

Starboard cleats



Supplied complete with backplate and rivets

CL233BP



CL233

Starboard cleats



CL212A

CL212

CL212BP

CL212BP-B

Starboard cleats



CL273

CL273AN

CL258

CL258AN

Backplate and Rivets fit CL212, CL214W, CL241, CL258, CL259 and CL273

Port cleats



CL241

CL241AN


CL259AN

CL214W



CL259



CL233 and CL241 can be fixed to the edge of the sail.



CL212
CL221
CL233
CL241
CL258



Most cleats can be sewn or rivetted.

Hard Anodised (AN) cleats look good on dark cloth and carbon fibre sails. They should be sewn onto carbon fibre sails as rivets can corrode.