

MLI-E 12/1200



Product code: 66011200

The Mastervolt MLI-E Lithium Ion battery closes the gap between the very compact MLS battery and the successful high capacity MLI Ultra series. The MLI-E is ideal for applications where long lifespan, light weight, fast charging and compactness are key. Its practical form factor makes the MLI-E perfectly suitable for mobile applications.

Compact, maintenance free power, ideal for mobile applications

Lithium Ion has many advantages over lead-acid. The MLI-E saves up to 70 % in space and weight, recharges in less than an hour, and deep cycles 5.000 times easily, which is up to 10 times longer than lead-acid batteries. The MLI-E can replace a 180-200 Ah lead-acid battery. Also, for the MLI-E the extremely safe Lithium Ion (LiFePO4) chemistry is used.

No external safety relay is needed. The MLI-E is protected against overcharging, deep discharging and overheating and comes with an integrated electronic safety switch. With its plastic case, the MLI-E is a straight-forward replacement for most lead-acid batteries.

LED indicators inform you about the actual status of your battery. Of course, the MLI-E is provided with integrated battery monitoring, including information about state of charge and time remaining. For optimal integration in both mobile and maritime power systems, both NMEA2000 / CZone and CANopen protocols are supported. Needless to say, the MLI-E fits perfectly into a MasterBus system, when combined with our system monitor EasyView 5*. And last but not least: hands-on monitoring is available, using Bluetooth and a mobile app.

Features

- Very long lifespan, maintenance free.
- Fast charging and discharging, fully charged within an hour.
- Straight-forward replacement for most existing lead-acid batteries (EqPb: 200 Ah).
- Compact, practical size.
- Extremely safe Lithium Ion chemistry (LiFePO4).
- Integrated safety switch for quick and easy installation.
- High performance even under harsh conditions.
- High efficiency and low self-discharge.
- Integrated battery monitoring for reliable battery status information.
- System integration via NMEA2000 / CZone, CANopen or MasterBus (via EasyView 5*).
- Monitoring via Bluetooth app possible.

Applications

Its size, weight, tough case and resistance to shocks makes the MLI-E ideal for mobile applications. Other applications range from marine, infrastructure, off-grid to industrial applications.

* Max. two MLI-E batteries per EasyView 5. Refer to manual for details.

Specifications

Communication & monitoring

Communication

LED indicators, CANopen, CZone/NMEA 2000 (through drop cable CZone/MasterBus, product code 77046000), MasterBus (through EasyView 5*, product code 77010310), Bluetooth (via mobile app)

General specifications

Nominal battery voltage	13.2 V
Nominal battery capacity	90 Ah
Nominal battery energy capacity	1200
Cycle life	
Max. charge current	90 A (1 C)
Continuous discharge current	200 A (2.2 C)
Peak discharge current	350 A (3,8 C) for 30 s
Battery monitoring	integrated
Battery terminals	automotive or M8 hexagon
Mounting position	mountable in multiple orientations, suitable for LN5 fastening brackets
Battery standard	Group 49, H8
Battery designation	IEC 62620: IFpR19/67[60p4s]M/-10+60/90 - IEC 61960: 4IFpR19/67-60
Max. outer dimensions (incl. terminals/grip handles), lxxwxh	353 x 175 x 190 mm 13.9 x 6.9 x 7.5 inch
Weight	12.5 kg 27.6 lb
Delivered with	2x automotive battery pole, 2x M8 bolt, hexagon tool, USB stick (with manual)

Technical specifications

Battery chemistry	Lithium Iron Phosphate (LiFePO4)
Temperature range (ambient temp.)	-20 °C to 60 °C (discharge), derating < 0 °C and > 45 °C / charge -10 °C to 45 °C, derating < 0 °C and > 45 °C °C -4 to 140 °F
Protection degree	IP51
Parallel connection	yes, unlimited
Series connection	no
Protections	over voltage, under voltage, over-temperature
Safety disconnect	automatic, integrated