









NAUTILUS EXHAUST LLOYDS APPROVED

MARINE DIESEL EXHAUST



Product Information

Order Ref:	MDE-SIZE MM
Tube:	BLACK, EXHAUST GAS, SALT WATER RESISTANT EPDM RUBBER
Reinforcement:	HIGH TENSILE SYNTHETIC TEXTILE FABRICS AND DOUBLE STEEL HELIX WIRE
Cover:	BLACK CORRUGATED, RESISTANT TO HEAT, SALT WATER, OZONE, ABRASION, EPDM RUBBER
Application:	MARINE DIESEL EXHAUST HOSE, CORRUGATED FOR MARINE CRAFT
Specification:	SAEJ2006R1 LLOYDS APPROVED

	 ID	 OD	 WP	 BP	 BR	 W/A	 VACUUM	 COIL
Inch	mm	mm	BAR	BAR	mm	gr/m	BAR	m
1	25	35	3	9	100	540	0.3	10/40
1 1/4	32	42	3	9	130	658	0.3	10/40
1 1/2	38	48	3	9	150	866	0.3	10/40
1 9/16	40	50	3	9	160	891	0.3	10/20
1 3/4	45	55	3	9	180	998	0.3	10/40
2	51	61	3	9	200	1126	0.3	10/40
2 1/4	57	67	3	9	220	1251	0.3	10
2 3/8	60	70	3	9	240	1312	0.3	10

2 1/2	64	74	3	9	250	1383	0.3	10
3	76	86	3	9	300	1612	0.3	10/20
3 1/2	90	101	3	9	360	2113	0.3	10
4	102	112	3	9	400	2351	0.3	10
5	127	139	3	9	500	3280	0.3	10
6	153	165	3	9	825	4157	0.3	10



-40°C to +100°C, peaks up to 115°C

Branding: NAUTILUS MARINE EXHAUST
Colour : BLACK