

Product Data

HEMPEL'S TEAK CLEANER 67543



Description:	HEMPEL'S TEAK CLEANER 67543 is a cleaning powder for teak. Especially suited for large areas like decks.
Recommended use:	For use on new wood as well as on previously treated wood, interior and exterior, above the waterline.
Availability:	Part of European Yacht assortment. Local availability subject to confirmation.
PHYSICAL CONSTANTS:	
Shade nos/Colours:	99980/ Off-white.
Finish:	Powder
Volume solids, %:	100
Flash point:	None.
Specific gravity:	2.3 kg/litre [19.2 lbs/US gallon]
VOC content:	0 g/l [0 lbs/US gallon]
Shelf life:	5 years 25°C/77°F
	<i>The physical constants stated are nominal data according to the HEMPEL Group's approved formulas.</i>
APPLICATION DETAILS:	
Application method:	Brush
Indicated film thickness, dry:	Not relevant
Indicated film thickness, wet:	Not relevant
Safety:	Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult HEMPEL Safety Data Sheets and follow all local or national safety regulations.

Product Data

HEMPEL'S TEAK CLEANER 67543



PRODUCT APPLICATION:	Method: Wet the surface with fresh water. Apply a layer of the product. Distribute the powder in a uniform layer with a brush. The surface must be sufficiently wet to keep the powder moist. After approximately 10-15 minutes, using a stiff brush, scrub while the powder is still moist. Clean the surface thoroughly with clean fresh water before the paste hardens. Treatment may be repeated if necessary. Avoid contact with stainless steel.
APPLICATION CONDITIONS :	Do not apply in direct sunlight.
RECOMMENDED DETERGENT :	HEMPEL'S PRE-CLEAN 67602
PRECEDING COAT:	None.
SUBSEQUENT COAT:	HEMPEL'S TEAK OIL 67571, HEMPEL'S TEAK COLOUR RESTORER 67462
REMARKS:	Harmless to glass fibre, painted or varnished surfaces. Use a wax or a polish to protect against contact with stainless steel. HEMPEL'S COLOUR RESTORER 67462 can be used on teak decks and other wood surfaces exposed to hard wear and tear ONLY if it is overcoated with HEMPEL'S TEAK OIL 67571.
Storage Conditions:	Exposure to air and temperature variances should be avoided. Avoid direct sunlight. Keep containers tightly sealed. Store at temperatures: 5°C/41°F - 35°C/95°F.
Overcoating:	Not relevant
Note:	HEMPEL'S TEAK CLEANER 67543
ISSUED BY:	HEMPEL A/S 6754399980

This Product Data Sheet supersedes those previously issued.

For explanations, definitions and scope, see "Explanatory Notes" available on www.hempel.com. Data, specifications, directions and recommendations given in this data sheet represent only test results or experience obtained under controlled or specially defined circumstances. Their accuracy, completeness or appropriateness under the actual conditions of any intended use of the Products herein must be determined exclusively by the Buyer and/or User.

The Products are supplied and all technical assistance is given subject to HEMPEL's GENERAL CONDITIONS OF SALES, DELIVERY AND SERVICE, unless otherwise expressly agreed in writing. The Manufacturer and Seller disclaim, and Buyer and/or User waive all claims involving, any liability, including but not limited to negligence, except as expressed in said GENERAL CONDITIONS for all results, injury or direct or consequential losses or damages arising from the use of the Products as recommended above, on the overleaf or otherwise. Product data are subject to change without notice and become void five years from the date of issue.