



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 14

TEROSON UP 150 CAN743G EGFD

SDS No. : 583758
V002.0

Revision: 20.12.2022

printing date: 21.12.2022

Replaces version from: 22.12.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TEROSON UP 150 CAN743G EGFD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
2K Filler paste

1.3. Details of the supplier of the safety data sheet

Henkel Ltd
Adhesives
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable liquids	Category 3
H226 Flammable liquid and vapour.	
Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Toxic to reproduction	Category 2
H361d Suspected of damaging the unborn child.	
Specific target organ toxicity - repeated exposure	Category 1
H372 Causes damage to organs through prolonged or repeated exposure.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:**Contains**

Styrene

Signal word:

Danger

Hazard statement:

H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H361d Suspected of damaging the unborn child.
 H372 Causes damage to organs through prolonged or repeated exposure.

**Precautionary statement:
Prevention**

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.

**Precautionary statement:
Response**

P302+P352 IF ON SKIN: Wash with plenty of water.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 IF exposed or concerned: Get medical advice/attention.

**Precautionary statement:
Disposal**

P501 Dispose of contents/container in accordance with national regulation.

2.3. Other hazards

Solvents contained in the product evaporate during processing and their vapors can form explosive/highly inflammable air/vapor mixtures.

The solvent vapors are heavier than air and may collect in high concentrations at floor level.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Declaration of the ingredients according to CLP (EC) No 1272/2008:**

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Styrene 100-42-5 202-851-5 01-2119457861-32	10- < 25 %	Flam. Liq. 3, H226 Acute Tox. 4, Inhalation, H332 Asp. Tox. 1, H304 Eye Irrit. 2, H319 Skin Irrit. 2, H315 STOT RE 1, Inhalation, H372 Repr. 2, H361d Aquatic Chronic 3, H412 STOT SE 3, H335		

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

IF ON SKIN: Wash with plenty of soap and water.

In case of adverse health effects seek medical advice.

Eye contact:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

Water

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Avoid contact with skin and eyes.

Keep unprotected persons away.

Danger of slipping on spilled product.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

Remove with liquid-absorbing material (sand, peat, sawdust).

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid open flames and sources of ignition.

Ground/bond container and receiving equipment.

Use explosion proof electric equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Temperatures between + 5 °C and + 35 °C

Keep container tightly sealed.

Store in a cool, dry place.

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

2K Filler paste

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Dolomite 16389-88-1 [DUST, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Dolomite 16389-88-1 [DUST, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Styrene 100-42-5 [STYRENE]	100	430	Time Weighted Average (TWA):		EH40 WEL
Styrene 100-42-5 [STYRENE]	250	1.080	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Dolomite 16389-88-1 [DUSTS NON-SPECIFIC]		4	Time Weighted Average (TWA):		IR_OEL
Dolomite 16389-88-1 [DUSTS NON-SPECIFIC]		10	Time Weighted Average (TWA):		IR_OEL
Styrene 100-42-5 [STYRENE]	20	85	Time Weighted Average (TWA):		IR_OEL
Styrene 100-42-5 [STYRENE]	40	170	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Styrene 100-42-5	aqua (freshwater)		0,028 mg/l				
Styrene 100-42-5	aqua (marine water)		0,014 mg/l				
Styrene 100-42-5	aqua (intermittent releases)		0,04 mg/l				
Styrene 100-42-5	sewage treatment plant (STP)		5 mg/l				
Styrene 100-42-5	sediment (freshwater)				0,614 mg/kg		
Styrene 100-42-5	sediment (marine water)				0,307 mg/kg		
Styrene 100-42-5	Soil				0,2 mg/kg		
Styrene 100-42-5	Air						no hazard identified
Styrene 100-42-5	Predator						no potential for bioaccumulation

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Styrene 100-42-5	Workers	Inhalation	Acute/short term exposure - systemic effects		289 mg/m3	no hazard identified
Styrene 100-42-5	Workers	Inhalation	Acute/short term exposure - local effects		306 mg/m3	no hazard identified
Styrene 100-42-5	Workers	dermal	Long term exposure - systemic effects		406 mg/kg	no hazard identified
Styrene 100-42-5	Workers	Inhalation	Long term exposure - systemic effects		85 mg/m3	no hazard identified
Styrene 100-42-5	General population	Inhalation	Acute/short term exposure - systemic effects		174,25 mg/m3	no hazard identified
Styrene 100-42-5	General population	Inhalation	Acute/short term exposure - local effects		182,75 mg/m3	no hazard identified
Styrene 100-42-5	General population	dermal	Long term exposure - systemic effects		343 mg/kg	no hazard identified
Styrene 100-42-5	General population	Inhalation	Long term exposure - systemic effects		10,2 mg/m3	no hazard identified
Styrene 100-42-5	General population	oral	Long term exposure - systemic effects		2,1 mg/kg	no hazard identified

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).

This recommendation should be matched to local conditions.

Hand protection:

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Fluorinated rubber (FKM; ≥ 0.7 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Fluorinated rubber (FKM; ≥ 0.7 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing that covers arms and legs.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Delivery form	paste
Colour	blue
Odor	characteristic
Melting point	Not applicable, Product is a liquid
Initial boiling point	115 °C (239 °F)
Flammability	flammable
Explosive limits	Currently under determination
Flash point	38 °C (100.4 °F)
Auto-ignition temperature	345 °C (653 °F)
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic) (20 °C (68 °F);)	> 20,5 mm ² /s ; Internal Henkel specification
Solubility (qualitative)	Currently under determination
Partition coefficient: n-octanol/water	Not applicable
	Mixture
Vapour pressure (20 °C (68 °F))	622 Pa
Vapour pressure (50 °C (122 °F))	3297 Pa
Vapour pressure (20 °C (68 °F))	2166 Pa
Vapour pressure (50 °C (122 °F))	11,42 kPa
Density (20 °C (68 °F))	1,80 - 1,90 g/cm ³ Internal Henkel specification
Relative vapour density:	Not available.
Particle characteristics	Not applicable
	Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with strong acids.

Reaction with strong bases

Reacts with alkalis.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Heat, flames, sparks and other sources of ignition.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

No decomposition if used according to specifications.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Styrene 100-42-5	LD50	6.600 - 8.000 mg/kg	rat	not specified

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Styrene 100-42-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Styrene 100-42-5	LC50	11,8 mg/l	vapour	4 h	rat	not specified

Skin corrosion/irritation:

No data available.

Serious eye damage/irritation:

No data available.

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Styrene 100-42-5	not sensitising	Guinea pig maximisation test	guinea pig	Magnusson and Kligman Method

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Styrene 100-42-5	positive	sister chromatid exchange assay in mammalian cells	with and without		OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells)
Styrene 100-42-5	negative	inhalation: vapour		mouse	not specified

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Styrene 100-42-5	not carcinogenic	inhalation: vapour	104 w 6 h/d, 5 d/w	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

No data available.

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Styrene 100-42-5	NOAEL 1.000 mg/kg	oral: gavage	78 w daily (5 d/w)	rat	not specified

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Styrene 100-42-5	LC50	4,02 mg/l	96 h	Pimephales promelas	EU Method C.1 (Acute Toxicity for Fish)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Styrene 100-42-5	EC50	4,7 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Styrene 100-42-5	NOEC	1,01 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Styrene 100-42-5	EC10	0,28 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)
Styrene 100-42-5	EC50	6,3 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	EPA OTS 797.1050 (Algal Toxicity, Tiers I and II)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Styrene 100-42-5	EC50	500 mg/l	30 min	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Styrene 100-42-5	readily biodegradable	aerobic	70,9 %	28 d	ISO DIS 9408 (Ultimate Aerobic Biodegradability Method by Determining the Oxygen Demand in a Closed Respirometer)
Styrene 100-42-5	inherently biodegradable	aerobic	100 %	14 d	OECD Guideline 302 C (Inherent Biodegradability: Modified MITI Test (II))

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Styrene 100-42-5	74				other guideline:

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Styrene 100-42-5	2,96	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Styrene 100-42-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

080111

SECTION 14: Transport information

14.1. UN number or ID number

ADR	1866
RID	1866
ADN	1866
IMDG	1866
IATA	1866

14.2. UN proper shipping name

ADR	RESIN SOLUTION
RID	RESIN SOLUTION
ADN	RESIN SOLUTION
IMDG	RESIN SOLUTION
IATA	Resin solution

14.3. Transport hazard class(es)

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable
	Tunnelcode: (D/E)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

When shipping as a set (component A and B), the following dangerous goods classification 'UN 3269 Polyester Resin Multi-Component System' can be used.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EU)	0 %

VOC Paints and Varnishes (EU):

Regulatory Basis:	Directive 2004/42/EC
Product (sub)category:	B(b) Bodyfiller/stopper
Phase I (from 1.1.2007):	250 g/l

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H361d Suspected of damaging the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.



Safety Data Sheet according to (EC) No 1907/2006 as amendedPage 1 of 15

TEROSON UP 150 CAN743G EGFD

SDS No. : 572846

V002.0

Revision: 20.12.2022

printing date: 21.12.2022

Replaces version from: 04.11.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TEROSON UP 150 CAN743G EGFD

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

hardener component

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Serious eye irritation

Category 2

H319 Causes serious eye irritation.

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Acute hazards to the aquatic environment

Category 1

H400 Very toxic to aquatic life.

Chronic hazards to the aquatic environment

Category 1

H410 Very toxic to aquatic life with long lasting effects.

Organic peroxides

Type E

H242 Heating may cause a fire.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:**Contains**

Dibenzoyl peroxide

Signal word:

Warning

Hazard statement:

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H410 Very toxic to aquatic life with long lasting effects.
 H242 Heating may cause a fire.

Precautionary statement:

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read label before use.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Precautionary statement:
Prevention**

P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P273 Avoid release to the environment.

**Precautionary statement:
Disposal**

P501 Dispose of contents/container in accordance with national regulation.

2.3. Other hazards

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Declaration of the ingredients according to CLP (EC) No 1272/2008:**

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Dibenzoyl peroxide 94-36-0 202-327-6 01-2119511472-50	45- 52 %	Org. Perox. B, H241 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 10 M chronic = 10	
Ethane-1,2-diol 107-21-1 203-473-3 01-2119456816-28	0,1- 9,9 %	Acute Tox. 4, Oral, H302 STOT RE 2, Oral, H373	oral:ATE = 500 mg/kg	EU OEL

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

IF ON SKIN: Wash with plenty of soap and water.

In case of adverse health effects seek medical advice.

Eye contact:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

SKIN: Rash, Urticaria.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Avoid contact with skin and eyes.

Keep unprotected persons away.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

Inform authorities in the event of product spillage to water courses or sewage systems.

6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Use only in well-ventilated areas.
Avoid open flames and sources of ignition.
Take measures to prevent the build-up of electrostatic charges.
No smoking.

Hygiene measures:

Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container.
Ensure good ventilation/extraction.
Store in a cool, dry place.
Temperatures between 0 °C and + 30 °C
Keep away from heat and direct sunlight.
Do not store together with food or other consumables (coffee, tea, tobacco, etc.).
Do not store together with oxidants.
Do not store together with reductants.

7.3. Specific end use(s)

hardener component

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Dibenzoyl peroxide 94-36-0 [DIBENZOYL PEROXIDE]		5	Time Weighted Average (TWA):		EH40 WEL
Dimethyl phthalate 131-11-3 [DIMETHYL PHTHALATE]		5	Time Weighted Average (TWA):		EH40 WEL
Dimethyl phthalate 131-11-3 [DIMETHYL PHTHALATE]		10	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Ethane-1,2-diol 107-21-1 [ETHANE-1,2-DIOL, PARTICULATE]		10	Time Weighted Average (TWA):		EH40 WEL
Ethane-1,2-diol 107-21-1 [ETHANE-1,2-DIOL, VAPOUR]	20	52	Time Weighted Average (TWA):		EH40 WEL
Ethane-1,2-diol 107-21-1 [ETHANE-1,2-DIOL, PARTICULATE]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Ethane-1,2-diol 107-21-1 [ETHANE-1,2-DIOL, VAPOUR]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Ethane-1,2-diol 107-21-1 [ETHYLENE GLYCOL]	40	104	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Ethane-1,2-diol 107-21-1 [ETHYLENE GLYCOL]	20	52	Time Weighted Average (TWA):	Indicative	ECTLV
Ethane-1,2-diol 107-21-1 [ETHANE-1,2-DIOL, VAPOUR]	40	104	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Dibenzoyl peroxide 94-36-0 [DIBENZOYL PEROXIDE]		5	Time Weighted Average (TWA):		IR_OEL
Dimethyl phthalate 131-11-3 [DIMETHYL PHTHALATE]		5	Time Weighted Average (TWA):		IR_OEL
Dimethyl phthalate 131-11-3 [DIMETHYL PHTHALATE]		10	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
Ethane-1,2-diol 107-21-1 [ETHYLENE GLYCOL]	40	104	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Ethane-1,2-diol 107-21-1 [ETHYLENE GLYCOL]	20	52	Time Weighted Average (TWA):	Indicative	ECTLV
Ethane-1,2-diol 107-21-1 [ETHANE-1,2-DIOL, VAPOUR]		20	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Ethane-1,2-diol 107-21-1 [ETHANE-1,2-DIOL]	20	52	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
Ethane-1,2-diol			Skin designation:	Can be absorbed through the	IR_OEL

107-21-1 [ETHANE-1,2-DIOL]				skin.	
Ethane-1,2-diol 107-21-1 [Ethane-1,2-diol]	40	104	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Dibenzoyl peroxide 94-36-0	aqua (freshwater)		0,00002 mg/l				
Dibenzoyl peroxide 94-36-0	aqua (marine water)		0,000002 mg/l				
Dibenzoyl peroxide 94-36-0	sewage treatment plant (STP)		0,35 mg/l				
Dibenzoyl peroxide 94-36-0	sediment (freshwater)				0,013 mg/kg		
Dibenzoyl peroxide 94-36-0	Soil				0,003 mg/kg		
Dibenzoyl peroxide 94-36-0	sediment (marine water)				0,001 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Dibenzoyl peroxide 94-36-0	Workers	Inhalation	Long term exposure - systemic effects		39 mg/m3	
Dibenzoyl peroxide 94-36-0	Workers	dermal	Long term exposure - systemic effects		13,3 mg/kg	
Dibenzoyl peroxide 94-36-0	Workers	dermal	Long term exposure - local effects		0,034 mg/cm2	
Dibenzoyl peroxide 94-36-0	General population	oral	Long term exposure - systemic effects		2 mg/kg	
Ethane-1,2-diol 107-21-1	Workers	dermal	Long term exposure - systemic effects		106 mg/kg	
Ethane-1,2-diol 107-21-1	Workers	inhalation	Long term exposure - local effects		35 mg/m3	
Ethane-1,2-diol 107-21-1	General population	dermal	Long term exposure - systemic effects		53 mg/kg	
Ethane-1,2-diol 107-21-1	General population	inhalation	Long term exposure - local effects		7 mg/m3	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure good ventilation/suction at the workplace.

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing that covers arms and legs.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	solid
Delivery form	paste
Colour	red
Odor	characteristic
Solidification temperature	Not applicable, Product is a solid.
Initial boiling point	Currently under determination
Flammability	Currently under determination
Explosive limits	Not applicable, Product is a solid.
Flash point	Currently under determination
Auto-ignition temperature	Not applicable, Product is a solid.
Decomposition temperature	50 °C (122 °F); Supplier method
pH	Product is non-soluble (in water).
Viscosity (kinematic)	Not applicable, Product is a solid.
Solubility (qualitative)	Insoluble
(23 °C (73.4 °F); Solvent: Water)	
Partition coefficient: n-octanol/water	Not applicable
	Mixture
Vapour pressure	Currently under determination
Density	1,1 g/cm ³ no method
(20 °C (68 °F))	
Relative vapour density:	Not applicable, Product is a solid.
Particle characteristics	Currently under determination

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity**10.1. Reactivity**

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

No decomposition if used according to specifications.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Dibenzoyl peroxide 94-36-0	LD50	> 2.000 mg/kg	mouse	OECD Guideline 401 (Acute Oral Toxicity)
Ethane-1,2-diol 107-21-1	Acute toxicity estimate (ATE)	500 mg/kg		Expert judgement

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Ethane-1,2-diol 107-21-1	LD50	10.600 mg/kg	rabbit	not specified

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Dibenzoyl peroxide 94-36-0	LC0	24,3 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Dibenzoyl peroxide 94-36-0	LC50	> 24,3 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Dibenzoyl peroxide 94-36-0	not irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Ethane-1,2-diol 107-21-1	not irritating	20 h	rabbit	BASF Test

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Dibenzoyl peroxide 94-36-0	not irritating		rabbit	FDA Guideline
Ethane-1,2-diol 107-21-1	not irritating		rabbit	BASF Test

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Dibenzoyl peroxide 94-36-0	sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Ethane-1,2-diol 107-21-1	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Dibenzoyl peroxide 94-36-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Dibenzoyl peroxide 94-36-0	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Ethane-1,2-diol 107-21-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Dibenzoyl peroxide 94-36-0	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Ethane-1,2-diol 107-21-1	negative	oral: feed		rat	Chromosome Aberration Test

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Dibenzoyl peroxide 94-36-0	not carcinogenic	dermal	2 y daily	rat	male/female	equivalent or similar OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Dibenzoyl peroxide 94-36-0	NOAEL P >= 1.000 mg/kg NOAEL F1 500 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Dibenzoyl peroxide 94-36-0	NOAEL 190 mg/kg	oral: feed	120 w daily	rat	not specified
Dibenzoyl peroxide 94-36-0	NOAEL > 833 mg/kg	dermal	104 w daily	mouse	OECD Guideline 451 (Carcinogenicity Studies)
Ethane-1,2-diol 107-21-1	NOAEL 150 mg/kg	oral: feed	16 w daily	rat	equivalent or similar to OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Dibenzoyl peroxide 94-36-0	LC50	0,06 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Ethane-1,2-diol 107-21-1	LC50	72.860 mg/l	96 h	Pimephales promelas	EPA-660 (Methods for Acute Toxicity Tests with Fish, Macroinvertebrates and Amphibians)
Ethane-1,2-diol 107-21-1	NOEC	15.380 mg/l	7 d	Pimephales promelas	other guideline:

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Dibenzoyl peroxide 94-36-0	EC50	0,11 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Ethane-1,2-diol 107-21-1	EC50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Dibenzoyl peroxide 94-36-0	EC10	0,001 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Ethane-1,2-diol 107-21-1	NOEC	8.590 mg/l	7 d	Ceriodaphnia dubia	other guideline:

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Dibenzoyl peroxide 94-36-0	ErC50	0,071 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Dibenzoyl peroxide 94-36-0	NOEC	0,02 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethane-1,2-diol 107-21-1	EC50	> 6.500 - 13.000 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Ethane-1,2-diol 107-21-1	NOEC	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Dibenzoyl peroxide 94-36-0	EC 50	35 mg/l	30 min	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Ethane-1,2-diol 107-21-1	EC20	> 1.995 mg/l	30 min	activated sludge, domestic	ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Dibenzoyl peroxide 94-36-0	readily biodegradable	aerobic	71 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Ethane-1,2-diol 107-21-1	readily biodegradable	aerobic	> 90 - 100 %	10 d	OECD Guideline 301 A (new version) (Ready Biodegradability: DOC Die Away Test)

12.3. Bioaccumulative potential

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
Dibenzoyl peroxide 94-36-0	66,6			fish	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Dibenzoyl peroxide 94-36-0	3,2	22 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Ethane-1,2-diol 107-21-1	-1,36		QSAR (Quantitative Structure Activity Relationship)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Dibenzoyl peroxide 94-36-0	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Ethane-1,2-diol 107-21-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

080409

SECTION 14: Transport information

14.1. UN number or ID number

ADR	3108
RID	3108
ADN	3108
IMDG	3108
IATA	3108

14.2. UN proper shipping name

ADR	ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)
RID	ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)
ADN	ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)
IMDG	ORGANIC PEROXIDE TYPE E, SOLID (DIBENZOYL PEROXIDE)
IATA	Organic peroxide type E, solid (Dibenzoyl peroxide)

14.3. Transport hazard class(es)

ADR	5.2
RID	5.2
ADN	5.2
IMDG	5.2
IATA	5.2 (HEAT)

14.4. Packing group

ADR
RID
ADN
IMDG
IATA

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable
	Tunnelcode: (D)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

When shipping as a set (component A and B), the following dangerous goods classification 'UN 3269 Polyester Resin Multi-Component System' can be used.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EU)	0 %

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H241 Heating may cause a fire or explosion.
H302 Harmful if swallowed.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.