

SmartRemote (OEM)



Product code: 77010500

Checking your Mastervolt product has never been easier

The SmartRemote completes any MasterBus or CZone* system. With its good looks and compact size, the SmartRemote is ideal as a remote panel in entry level power systems or as a local device readout in larger systems. Applications include boats, vehicles and stationary systems.

Local device monitoring

Mastervolt products enable intelligent power systems with advanced multi-device monitoring and control. However, in situations where the local device readout is hard to reach or too limited, an entry-level color display for local device monitoring would be ideal. This is where the SmartRemote comes in.

Easy to use

The new SmartRemote single-device display is unique in many ways. It communicates with Mastervolt devices**, shows key parameters, allows simple device settings and is fun to use. Checking your batteries, adjusting your shore fuse or controlling your Mastervolt charger/inverter has never been easier.

Easy to install

The SmartRemote display can be panel mounted or may be integrated into a Blue Sea Systems Custom 360 bezel. Connection is easy as 1-2-3: simply click the network cable into a Mastervolt device and off you go.

Features

- Full color display for local device monitoring.
- Displays four key parameters.
- Control key device functions.
- CZone* and MasterBus network compatible.
- Universal, easy mounting.
- Plug & Play – no configuration, no power supply needed.
- Blue Sea Systems Custom 360 integration.

Think Global, Act Local... Smart Remote!

(*) Full CZone compatibility expected September 2019.

(**) SmartRemote supports CombiMaster communication over the MasterBus network. Support for Mastervolt battery chargers, inverters, charger/inverters, MLI batteries and MasterShunt devices is under development. Wondering if your device is supported? Check the Downloads section below or contact your dealer.

Specifications

General specifications

Interfaces	CZone, MasterBus
Display/read-out	2.8 inch, 320 x 240 pixels, high colour
Mounting	panel mount (cutout: Ø 52 mm / 2 inch, 4 screws included); Blue Sea 360 panel mount (locking ring included)
Protection degree	IP20
Dimensions, hxxwxd	72 x 72 x 29.4 mm
	2.8 x 2.8 x 1.2 inch
Weight	0.075 kg
	0.2 lb
Delivered with	OEM package includes 10 pcs. SmartRemote displays only, no MasterBus or Mastervolt-CZone drop cables are included. Please order the cables separately when needed.

Technical specifications

Power consumption	Bus powered, < 160 mW (idle mode)
-------------------	-----------------------------------