

- Ideal for vessels less than 20M in length.
- Deck Floodlight and Masthead lamp combined in one robust housing.
- Flexible mounting arms for mounting on a variety of mast profiles.
- Illuminates large areas of deck or superstructure.
- Meets EMC EN60945, USCG & ABYC A-16



### FEATURES

- Ideal for vessels less than 20M in length.
- Deck Floodlight and Masthead lamp combined in one robust housing.
- Flexible mounting arms for mounting on a variety of mast profiles.
- Illuminates large areas of deck or superstructure.
- Meets EMC EN60945, USCG & ABYC A-16

### SPECIFICATION

Nominal/ Input DC Voltage	9-33V
Nominal Current at	0.37A@12V
Power Consumption	4.5W
LED	1W, white (5000~6500K)
LED Q'ty	2pcs—Masthead lamp / 4pcs—Foredeck lamp
View Angle	225° (Masterhead lamp)
Housing	PA66, black/ white
Lens	PMMA, clear
Minimum Visible Distance	3NM (Masterhead lamp)
IP Rating	67
Cable Length (cm)	30
Size (mm)L x W x H	83 x 83 x 65/ Pole: 204.89(8")/ 305.69(12")/ 610.7(24")
Operation Temperature	-20°C~ +60°C

