


## SWA6 COMBINED BLUETOOTH STEREO SUBWOOFER



Connect smartphones and MP3 players to the subwoofer via Bluetooth or RCA inputs



Built-in 288W amplifier powers the internal subwoofer and external speakers



Connect up to four speakers (sold separately)

**Halo Aerial Technology** provides unrivalled Bluetooth range and signal strength

**Tuned port** for outstanding subwoofer performance

**Electronic Crossover** automatically balances speaker and subwoofer for optimum performance

### KEY FEATURES

**Bluetooth** **Bluetooth Audio** Easily stream your favorite tunes direct from your smartphone to the SWA6 with Bluetooth Audio support.

**HALO AERIAL TECHNOLOGY** **Halo Aerial Technology** Receive a stronger Bluetooth signal and greater range in all directions over standard Bluetooth with Halo Aerial Technology.

**TUNED PORT** **Tuned Port** provides outstanding subwoofer performance, showcasing your favorite music in all its sonic glory.

**Remote Ready** Connect wired or wireless remote controls for an easier listening experience with the ability view track info and control your SWA6's features.

**Electronic Crossover** Automatically balanced speaker and subwoofer outputs for no-hassle perfect sound quality across across all frequencies.

**288W POWER** **288W Amplifier** Built-in 288W Amplifier powers both the internal subwoofer and up to four external speakers (sold separately).

**AUX** **AUX** Connect devices via stereo RCA cable with variable input gain of 400mv, 2V or 4V available for optimum performance with all devices.

**2 YEAR WARRANTY** **2 Year Warranty** Aquatic AV products are built to be reliable and durable. The SWA6 comes with a two year warranty that can be extended with product registration.

## SPECIFICATIONS

Type:	Bluetooth Ready Active Subwoofer with full range speaker output
Subwoofer Cone Size:	8"
Subwoofer Frequency Response:	26 - 125 Hz
Impedance:	4 Ohm & 2 Ohm stable
Sensitivity:	86dB
Power (max):	288W
Waterproof:	IPx4
Chassis Material:	ABS
Cone Material:	Polypropylene
Inputs:	Bluetooth 2x RCA with variable 400mv, 2V or 4V input for optimum performance with all devices
Outputs:	2 channel full range output
Frequency Response (amp):	125 - 20,000 Hz
Amplifier Power (max):	72W x 2 (@ 2 Ohms) / 45W x 2 (@4 Ohms)
Certification:	RoHS
Dimensions:	368.3 x 279.4 x 144.2 mm
Additional Features:	Tuned port Pre-balanced electronic cross-over

## DIMENSIONS

