

Temperature Senders

Veethree Temperature Senders are robust and reliable units for measuring the temperature of various fluids. These units are ideal for automotive, industrial machinery, agricultural, marine and off road equipment application where long-term performance under demanding conditions is required.



NPT Designation	Inside Diameter	Outside Diameter	Outside Diameter
1/8-27	1/8 in.	0.40 in.	13/32 in.
1/4-18	1/4 in.	0.50 in.	35/64 in.
3/8-18	3/8 in.	0.675 in.	43/64 in.
1/2-14	1/2-in.	0.84 in.	27/32 in.

AT A GLANCE

FEATURES

- Brass housing is corrosion resistant.
- European and US standard matches are available
- Metric threads are available upon request
- Designed to work with 12 and 24 volt systems.
- Sender / Switch combinations available.

Part Number	Temperature Range	Threading	Type
52320-032	100 - 230 Degrees F	3/8"-18 NPT	S/W®
VEM757096	100 - 240 Degrees F	1/8"-27 BSPT	S/W®
52320-010	100 - 240 Degrees F	1/8"-27 NPT	S/W®
52320-004	100 - 240 Degrees F	1/4"-18 NPT	S/W®
52320-018	100 - 240 Degrees F	3/8"-18 BSPT	S/W®
52320-009	100 - 240 Degrees F	3/8"-18 NPT	S/W®
52320-003	100 - 240 Degrees F	1/2"-14 NPT	S/W®
52320-026	100 - 260 Degrees F	3/8"-18 NPT	S/W®
52320-028	100 - 280 Degrees F	1/8"-27 NPT	S/W®
52320-005	100 - 280 Degrees F	1/2"-14 NPT	S/W®
52320-012	100 - 360 Degrees F	3/8"-18 NPT	A/C 89 Series®
52320-011	100 - 360 Degrees F	1/2"-14 NPT	A/C 89 Series®
52320-001	120 - 230 Degrees F	1/2"-14 NPT	S/W®
52320-006	140 - 320 Degrees F	1/8"-27 NPT	S/W®
52320-008	140 - 320 Degrees F	3/8"-18 NPT	S/W®
52320-002	140 - 320 Degrees F	1/2"-14 NPT	S/W®